

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 544400

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 23 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original -Nathaniel Ford, under Contract #44, dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6525)

-----  
(Common Corner)

Set  $\frac{1}{4}$  sec.post, at average distance, from which

A B.Oak 10" dia., bears N.5°W., 20 lks.

A B.Oak 7" dia., bears S.35°E., 63 lks.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 & 15 Page(s) 5943 & 5973)

-----  
(On page 5943, Mensch searched for, could not find orig. cor.)

On Page 5973:

Set an Iron post, 3 ft. long 1" dia., 28" in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 23 only, with brass cap marked:

-----  
 $\frac{1}{4}$  S 23  
1924

from which

A Fir 14" dia., bears S.11°E., 42 lks. mkd.  $\frac{1}{4}$  S23 BT.

A W.Oak 6" dia., bears S.34°W., 51 lks. mkd.  $\frac{1}{4}$  S23 BT.

Douglas Co. Surveyors Office - Karen Reed; Frank Silagy - Feb. 15, 1979 - C.S. File 60/24-11

-----  
CONDITION REPORT ONLY. NO MONUMENT OR NEW ACCESSORIES SET.

Found - A 1924 GLO brass cap properly marked, protruding 23" above ground in a mound of stone.

A 14" D.Fir now 22" bears S.11°E., 27.7 ft. with well healed double blaze.

A 6" B.Oak now 8" (Rec. W.Oak), bears S.34°W., 33.6 ft. with well healed blaze.

An unrecorded 10" D.Fir bears N.65°W., 11.0 ft. healed over blazes on South, West and East sides.

FD. OK, BLM in 1981, Jelley/Rogers. DCSO Records. Vol. 43 Pg. 16672.

Fd. OK, April 1991, M 113-6