

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM survey by Roy T. Campbell, under Contract #789 dated Aug. 21, 1910 (DCSO records Vol. 15 Page(s) 6558)

Set a diorite stone, 12x 10 x 8", 8" in the ground, for 1/4 sec. cor., mkd. 1/4 on W. face, from which
A Fir 8" dia., bears S.9°E., 43 lks. dist., mkd. 1/4 S36 BT
A Fir 18" dia., bears S.52°15'W., 25 lks. dist., marked 1/4 S 35 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - April/May 1962 - C.S. File 49/139-54

Found - Stone, as recorded at cor. SE BT shows scar. SW BT, now down, center rotted.
Set (1924?) brass cap alongside corner stone and marked
County Surveyors Office 1962
1/4 S35 | S36 T29S R7W
New BTs -Remark O.B.T., now 22" Hemlock S.11°E., 28.4 ft. "1/4 S36 CS BT".
9" Chinquapin bears N.51°W., 26.0 ft. scribed 1/4 S35 CS BT.

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed July 2002, - (DCSO records Vol. 54 Page(s) 21141-2)

The 1/4 sec. cor. of secs. 35 & 36, perpetuated by the Doug. Co. Surveyors Office, in 1962, monumented with the original diorite stone, firmly set, showing 5x9x3" above ground, with marks 1/4 visible on the N. face, from which the remaining original bearing tree
A hemlock, 28" dia., bears S.4 1/4°E., 28.7 ft., with a healed blaze. (Record, fir, S.9° E., 28.4 ft.)
and a BT mkd. by the Douglas County Surveyors Office
A chinquapin, 12" dia., bears N.40 3/4°W., 26.2 ft., with fragmentary scribe marks visible on partially healed double blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd. T29S R7W
S 35 | S 36
1/4
2002
Bury the orig. stone, 12x9x5" (record, 12x10x8"), inverted alongside and deposit a magnet in a white plastic case at the base of the iron post.
continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, an iron pipe, 1¼" dia., firmly set, projecting 14" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T29S R7W ¼ S35 S36 1962, bears North, 0.65 ft. This monument is recorded as being set alongside the original cor. stone and is not accepted as the true cor. location. At the request of the Douglas County Surveyors Office, the brass cap was removed and buried alongside the stainless steel post. A yellow plastic cap, 1¼" dia., mkd. DOUG CO SURVEYOR, was placed on top of the pipe, now projecting 2" above ground.

The geographic position (NAD 1983 (CORS)) of this cor. as determined by NAVSTAR GPS, utilizing dual frequency, carrier phase GPS receivers, (Trimble 5700), relative to the National Spatial Reference System, is as follows:
Latitude: 43°00'22.72"N., Longitude: 123°29'07.64"W.