

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 & 36

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

BLM survey by Roy T. Campbell, under Group #789 dated Aug. 21, 1910 (DCSO records Vol. 15 Page(s) 6556-67)

At the point of intersection
I set a granite stone, 15 x 12 x 4 ins., 10" in the ground for cor. of secs. 25, 26, 35 and 36, marked with 1 notch in S. and E. edges, from which
A Fir 18" dia., bears N.79°30'E., 56 lks. dist., mkd. T29S R7W S25 BT.
A Fir 6" dia., bears S.22°15'E., 29 lks. dist., mkd. T29S R7W S36 BT.
A Fir 12" dia., bears S.19°30'W., 53 lks. dist., mkd. T29S R7W S35 BT.
A Fir 30" dia., bears N.61°30'W., 29 lks. dist., mkd. T29S R7W S26 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - April/May 1962 - C.S. File 49/139-54

Found - Stone at corner as of record. Also SE & SW orig. BTs, each shows good scars. Orig. NE BT, now snag. Orig. NW BT, now stump.
Set Brass cap alongside corner stone mkd: S26|S25 T29S R7W
County Surveyors Office 1962 S35|S36
New BTs -14" Cedar bears N.59°E., 64.0 ft. scribed S25 T29S R7W CS BT.
11" R.Fir bears N.26°W., 66.2 ft. scribed S26 29S R7W CS BT.

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed July 2002, - (DCSO records Vol. 54 Page(s) 21142-3)

The cor. of secs. 25, 26, 35, & 36, perpetuated by the Douglas County Surveyors Office, in 1962, monumented with the original granite stone, firmly set, showing 8x6x2" above ground, with 1 notch on S & E edges visible, from which the remains of the original bearing trees
A fir, 24" dia., bears S.22¼°E., 19.1 ft. with a healed blaze.
A fir, 28" dia., bears S.19½°W., 35.0 ft., with a healed blaze.
A sawed fir stump, 40" dia., bears N.61½°W., 19.1ft., with no marks visible.
and bearing trees mkd. by the Douglas County Surveyors Office
A cedar, 28" dia., bears N.58¾°E., 63.5 ft., with a healed blaze.
continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 24" dia., bears N.27½°W., 66.2 ft., with a healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T29S R7W
S 26 | S 25
S 35 | S 36
2002

Bury the original stone, 11x8x6" (record, 15x12x4"), inverted alongside and deposit a magnet in a white plastic case at the base of the iron post.

From this point, an iron pipe, 1¼" dia., firmly set, projecting 13" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T29S R7W S25 S26 S35 S36 1962, bears West, 0.50 ft. This monument is recorded as being set alongside the original cor. stone and is not accepted as the true cor. location. At the request of the Douglas County Surveyors Office, the brass cap was removed and buried alongside the stainless steel post. A yellow plastic cap, 1¼" dia., mkd. DOUG CO SURVEYOR, was placed on top of the pipe, now projecting 2 ins. above ground.

Corner is located 1 ft. West of the cor. of 4 strand barbed wire fences which extend North, East, and West.

The geographic position (NAD 1983 (CORS)) of this cor. as determined by NAVSTAR GPS, utilizing dual frequency, carrier phase GPS receivers, (Trimble 5700), relative to the National Spatial Reference System, is as follows:

Latitude: 43°00'48.84"N., Longitude: 123°29'07.61"W.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22740-1)

The cor. of secs 25, 26, 35, & 36 monumented with a stainless steel post, 2½" dia., firmly set, projecting 2" above ground (alongside of which is an iron pipe, 1¼" dia., firmly set, projecting 2" above ground, with yellow plastic cap mkd DOUG CO SURVEYOR), with brass cap (properly) mkd from which the remains of the original bearing trees

A fir 25" dia. bears S.22¼°E. 19.1 ft. with a healed blaze.

A fir 30" dia. bears S.19½°W., 35.0 ft with a healed blaze

A sawed fir stump, 40" dia bears N61½°W., 19.1 ft. with a healed blaze.

and BTs mkd by the Douglas County Surveyors Office, in 1962

A cedar, 29" dia. bears N.58¾°E., 63.5 ft. with a healed double blaze.

continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 & 36

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

A fir, 26" dia., bears N.27½°W., 65.8 ft. with a healed blaze. (Record, 66.2 ft.)
Corner is located W., 1 ft. from the intersection of barbed wire fences extending N., E., and W.
The corner of sections 25 26 35 and the 36:
Latitude: 43°00'48.85" N. Longitude: 123°29'07.62"W.
(NAD 1983 (CORS))