

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Roy T. Campbell, under Group #789 dated Aug. 21, 1909 (DCSO records Vol. 15 Page(s) 6561)

-----  
Set a basalt stone, 15 x 10 x 6 ins., 10" in the ground, for corner of secs. 23, 24, 25 and 26, marked with 2 notches on S. and 1 notch on E. edge, from which

A Madrona 24" dia., bears N.84°30'E., 44 lks. mkd. T29S R7W S24 BT.

A Fir 6" dia. bears S.54°45'E. 41 lks mkd. T29S R7W S25 BT

A Fir 18" dia., bears S.15°W., 42 lks. dist., mkd. T29S R7W S26 BT.

A Fir 12" dia., bears N.16°30'W., 29 lks. dist., mkd. T29S R7W S23 BT.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - May 1962 (Added 5/10/2021) - C.S. File 51/163-2

-----  
Found - Stone 15" by 10" by 6"  
24: Madrone N.84½°E., 44 lks. (Good condition)  
6" Fir S.54¾°E., 41 lks. (Stump)  
18" fir S.15°W., 42 lks. (Gone)  
12" fir N.16½°W., 29 lks. (Stump)

Set - 1¼" by 24" iron pipe.  
Scribed- 10" D.Fir S.59½°E., 50.8 ft.  
14" D.Fir S.31½°W., 52.0 ft.  
14" D.Fir N.82°W., 15.5 ft.

Douglas Co. Surveyors Office - John M. Powell; Frank Jones; W. Penley - Oct. 15, 1969 - C.S. File 49/139-127

-----  
Found - 1½" Iron pipe at corner, unrecorded. (See above)  
Orig. 12" D.Fir, now stump, N.16½°W., 19.1 ft. scribe visible.  
Orig. 24" Laurel, now dead, N.84½°E., 29.0 ft. scribe visible.  
Unrecorded 13" D.Fir now stump burnt face, scribe visible.

Set Brass cap at cor. mkd: County Surveyor's T 29 S R 7 W  
Office S 23 | S 24  
1969 S 26 | S 25

New BTs -30" D.Fir N.21°W., 117.3 ft. scribed "T29S R7W S23 CS BT"

15" D.Fir N.59°W., 80.8 ft. scribed "T29S R7W S23 CS BT"

No other trees available for this corner.

continued next page

PRIMARY CORNER DESCRIPTION Sec Cor. for 23, 24, 25, and 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM resurvey by Jelley/Rogers, under Group #1044 - Surveyed, Jan/April 1981 (DCSO records Vol. 43 Page(s) 16666)

-----  
The Cor. of secs. 23, 24, 25 and 26, perpetuated and recorded by Powell in 1969, monumented with an I.P., firmly set, projecting 14" above ground, with properly mkd. brass cap. from which the remains of the original bearing trees

A root hole, bears N.88½°E., 44 lks. dist., with a down madrone alongside, 40" dia., no marks visible. (Rec. N.84½°E.)

A sawed fir stump, 24" dia., bears S.57°E., 41 lks. dist., with healed blaze. (Rec. S.54 ¾°E.)

A sawed Fir stump 28" dia., bears N.16½°W., 29 lks. dist. with illegible scribe marks visible on decayed blaze. and the remains of bearing trees mkd. by Powell

A sawed Fir stump 20" dia., bears N.59°W., 122 lks. dist., with healed blaze.

A Fir 36" dia., bears N.21°W., 177 lks. with healed blaze. and the remains of a bearing tree recorded by Powell

A sawed Fir stump 13" dia., bears N.84°W., 23 lks. dist., with illegible scribe marks visible on burned blaze. and a new bearing tree

A Fir 14" dia., bears N.58°W., 166 lks. dist., mkd. T29S R7W S23 BT.

No other suitable trees available within limits.

Fd. OK, August 1989, Howard Johnstone, M 101-60

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22742-3)

-----  
The cor. of secs. 23 24 25 & 26, monumented with an iron post ¾" dia. firmly set, projecting 14" above ground (alongside of which is an iron pipe, 1½" dia., projecting 8" above ground), with brass cap (properly) mkd. from which the remains of the original bearing trees

A sawed fir stump, size indeterminate bears S.57°E., 27.1 ft., with scribe marks T29S R7W S25 T visible on a partially healed blaze.

A sawed fir stump, size indeterminate bears N.16½°W. 19.1 ft., with scribe marks 7W visible on an open blaze. and the remains of a BT mkd. by person(s) unknown reported by Jelley and Rogers

A sawed fir stump, 18" dia. bears N.84°W., 15.2 ft. with no marks visible.

and the remains of bearing trees mkd. by Powell in 1969  
continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 18" dia., bears N.59°W., 80.5 ft., with no marks visible.  
A fir, 36" dia bears N.21°W., 116.8 ft with a healed blaze and the remains of a bearing tree mkd. by Jelley and Rogers  
A fir, 18" dia bears N.58°W. 109.6 ft with a healed blaze and new bearing trees  
A fir, 10" dia., bears N.29¾°E., 18.6 ft., mkd. T29S R7W S24 BT.  
A fir, 4" dia., bears S.68¾°E., 28.6 ft., mkd. X BT.  
A fir, 14" dia., bears S.38¾°W., 9.8 ft., mkd. T29S R7W S26 BT.

Fd. as per 2011 BLM resurvey by D Edwards, 6/2016 - M172-16