TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Roy T. Campbell, under Group #789 dated Aug. 21 1909, (DCSO records Vol. 15 Page(s) 6562)

Set a Fir post, 4" square 3 ft. long, 24" in the ground, for ¼ sec. cor., marked ¼ S23 on W., and 24 on E. face, from which

A Fir 24" dia., bears S.52°30'E., 49 lks. dist., mkd. ¼ S24 BT.

A Fir 14" dia., bears N.26°30'W., 26 lks. dist., mkd. ¼ S23 BT.

Douglas Co. Surveyors Office - John Powell; Frank Jones; W. Penley - Oct. 15, 1969 - C.S. File 49/139-125

Found - 14" now 16" D.Fir N.26½°E., 32.3 ft. opened for scribe.
24" D.Fir, now stump, S.52½°E., 32.3 ft. opened for scribe.

Set Brass cap at cor. mkd: County Surveyors Office, 1969 T 29 S R 7 W ¼ S 23|S 24

New BT - 18" D.Fir N.61°E., 29.0 ft. mkd. "¼ S24 CS BT".

Fd. OK, August 1989 by Howard Johnstone - M 101-60

BLM survey by Jelley/Rogers, under Group #1044 - Surveyed, Jan/April 1981 (DCSO records Vol. 43 Page(s) 16689)

From the ¼ sec. cor., perpetuated and recorded by Powell in 1969, monumented with an I.Post, firmly set, projecting 14" above ground, with brass cap properly marked.

from which the remains of the original bearing trees:

A sawed Fir stump, size indeterminate, bears S.52½°E., 49 lks., no marks visible.

A Fir 16" dia., bears N.26½°W., 26 lks. with healed blaze.

and a new bearing tree:

A Fir 9" dia., bears S.16°E., 43½ lks., mkd. ¼ S24 BT.

David Edwards - For: Seneca Jones Tmbr Co. - 5/2020 - M177-4

Found - 1969 DCS Brass cap
16" dia., Fir with healed blaze, bears N.26½°W., 17.2 ft. (OBT)
20" dia., Fir stump bears N.61°E., 29.0' (1969 DCS)
19" dia., Fir with healed blaze, bears S.16°E., 28.7' (1981 BLM)

Set - A six foot steel post is set 2 ft North.