

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854) (DCSO records Vol. 15 Page(s) 6525)

-----  
Set 1/4 sec. post, from which  
A Fir 24" dia., bears S.35°W., 18 lks. dist.  
A Laurel 12" dia., bears N.10°E., 35 lks. dist.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page 5943), searched for Ford's 1/4 corner, but fail to find any evidence.

BLM survey by Hans Theilsen, under Group #346, Surveyed, 1957) (DCSO records Vol. 28 Page(s) 12148)

-----  
Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:

T29S R7W

1/4

S14|S13

1957

from which

A Fir 8" dia., bears S.38°E., 53 lks. mkd. 1/4 S13 BT.

A Fir 14" dia., bears N.72°W., 108 lks. mkd. 1/4 S14 BT.

BLM resurvey by Theilsen, under special instructions and Group #346, Surveyed, 1959 (DCSO records Vol. 30 Page(s) 12805)

-----  
Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:

T29S R7W

1/4

S14|S13

1957

from which

A Fir 6" dia., bears S.47°E., 62 lks. mkd. 1/4 S13 BT.

A Fir 8" dia., bears N.71°W., 98 lks. mkd. 1/4 S14 BT.

Destroy bearing trees marked in 1957.

Fd. OK, April 1991, M 113-6

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Stephen J. Flause - John A. Pike- 04/14/1999 - C.S. File 66/8-37

Found - From the 1959 BLM resurvey a 2½ inch diameter brass cap (marked as below) on a 1 inch o.d. iron pipe firmly set and protruding approximately 19 inches above ground (this monument was moved from the position established in the 1957 BLM resurvey.

U.S. GENERAL LAND OFFICE SURVEY  
T29S R7W  
¼  
S14|S13  
1957

No evidence of original bearing trees is found. Bearing trees for the 1957 BLM resurvey were noted as destroyed in the 1959 BLM resurvey; possible evidence of the southeast 1957 B.T., with a previously chopped-out blaze, is found north from the 1959 southeast B.T..

From the 1959 BLM resurvey, two BTs are found:  
A fir 6" diam. now a 10 inch D.B.H. D.Fir with a fully healed single blaze, bears S.47°E., 40.9 feet distant (as per record).

A fir 8" diam. now a 29 inch D.B.H. D.Fir with a fully healed single blaze, bears N.71°W., 64.7 feet distant (as per record).

New BTs- An 11 inch D.B.H. Incense Cedar scribed "¼ S13 CS BT" on a double blaze, bears N.43½°E., 5.5 feet distant.

A 10 inch D.B.H. Douglas fir scribed "¼ S14 CS BT" on a double blaze, bears S64½W, 21.5 ft. dist.

Location & Comments -

Monument is on a very gentle south slope, on a blazed north-south line forming boundary between old and younger forest.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22746)

The ¼ sec. cor. of secs. 13 & 14, perpetuated by the Douglas County Surveyor's Office in 1999, monumented with an iron post, 1" dia., firmly set, projecting 19" above ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Thielsen in 1957

A fir, 11" dia., bears S.47°E., 40.9 ft., with a healed blaze.

continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 32" dia., bears N.71°W., 64.7 ft., with a healed blaze.  
and BTs mkd. by the Douglas County Surveyor's Office  
A cedar, 13" dia., bears N.43½°E., 5.6 ft., with scribe marks ¼ S13 CS BT visible on an open blaze.  
A fir, 12" dia., bears S.64¼°W., 22.1 ft., with a healed double blaze.  
Latitude: 43°02'59.92" N. Longitude: 123°29'07.80"W.  
(NAD83 (CORS))