

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Group #44 dated May 30, 1854
(DCSO records Vol. 15 Page(s) 6525-26)

Set a post, cor. of secs. 11, 12, 13 and 14, from which
A Red Fir 36" dia., bears S.43°E., 19 lks.
A Red Fir 24" dia., bears N.7°E., 43 lks.
A Laurel 6" dia., bears N.55°W., 29 lks.
A Red Fir 24" dia., bears S.48½°W., 63 lks.

GLO survey by Mensch under Instructions dated April 18, 1924
(DCSO records, Vol. 14, Page 5943) searched for, could find
no evidence of corner.

BLM survey by Hans Theilsen, under Group #346 - Surveyed
April/May 1957 (DCSO records Vol. 28 Page(s) 12148-49)

Point for cor. of secs. 11, 12, 13 and 14, at proportionate
distance; here is no remaining evidence of the orig. corner.
Set an iron post, 3 ft. long, 2" dia., 28" in the ground,
with brass cap marked:
T29S R7W
S 11|S 12
S 14|S 13
1957

from which
A Fir 9" dia., bears N.47°E., 180 lks. dist. mkd. T29S R7W
S12 BT.
A Fir 9" dia., bears S.33°E., 93 lks. dist. mkd. T29S R7W
S13 BT.
A Fir 8" dia., bears S.32°W., 78 lks. dist., mkd. T29S R7W
S14 BT.
A Fir 11" dia., bears N.73°W., 83 lks. dist., mkd. T29S
R7W S11 BT.

BLM survey by Hans Theilsen, under Special Instructions and
Group #346, Surveyed, Aug. 1959 (DCSO records Vol. 30 Page(s)
12806)

Point for cor. of secs. 11, 12, 13 and 14, at proportionate
distance; there is no remaining evidence of the orig. corner.
Set an iron post, 3 ft. long, 2" dia., 28" in the ground,
with brass cap marked:
T29S R7W
S 11|S 12
S 14|S 13
1957

from which
A Fir 9" dia., bears N.51°E., 200 lks. mkd. T29S R7WS12 BT
A Fir 9" dia., bears S.44°E., 110 lks. mkd T29S R7W S13 BT
(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 8" dia., bears S.15°W., 74 lks. dist., mkd. T29S R7W S14 BT.
A Fir 11" dia., bears N.66½°W., 61 lks. dist., mkd. T29S R7W S11 BT.

Corner Fd. OK, BLM survey by Rogers in 1984/85. (DCSO records, Vol. 47 Pages 17977-79)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22746)

The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2" dia., firmly set, projecting 7 ins. above ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Thielsen in 1957

A fir, 17" dia., bears N.53°E., 125.8 ft., with a healed blaze. (Record, N.51°E., 132.0 ft.)

A fir, 20" dia., bears S.44°E., 72.6 ft., with a healed blaze.

A fir, 26" dia., bears S.15°W., 46.2 ft., with a healed blaze.

A fir, 24" dia., bears N.66½°W., 40.3 ft., with a healed blaze.

Corner is located on a N. slope at the intersection of a broken down barbed and woven wire fences extending N, E, & W.