

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 11 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Group #44 dated May 30, 1854 (DCSO records Vol. 15 Page(s) 6526)

Set 1/4 sec. post, from which
A B.Oak 10" dia., bears S.33°E., 21 lks. dist.
A B.Oak 18" dia., bears N.21°E., 9 lks. dist.

BLM resurvey by Hans Theilsen, under group #346 - Surveyed April/May 1957 (DCSO records Vol. 28 Page(s) 12150)

Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:
T29S R7W
1/4
S11|S12
1957

from which
A Fir 9" dia., bears N.43°E., 40 lks. mkd. 1/4 S12 BT.
A Madrona, 40" dia., bears S.6°W., 67 lks. mkd. 1/4 S11 BT

BLM resurvey by Hans Theilsen, under Special Instructions and Group #346 - Surveyed Aug 1959 (DCSO records Vol 30 Pg 12807)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:
T29S R7W
1/4
S11|S12
1957

from which
A Fir 8" dia., bears N.50°E., 50 lks. mkd. 1/4 S12 BT.
A Madrone 40" dia., bears S.5°W., 74 lks. mkd. 1/4 S11 BT.

BLM Subdivision of Sec. 11 by Wayne Rogers, under Group #1208 - Surveyed Aug. 1984-Jan. 1985 (DCSO records Vol 47 Pg 17982)

Found Thielsen's brass cap and
A Fir 16" dia., bears N.54°E., 46 lks. dist., with healed blaze. (Rec. N.43°E., 40 lks.) (1957 record. V.L.)
Madrone, 42" dia., bears S.1°W., 67 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, S.6°W.) (1957 record - V.L.)

continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22747)

The ¼ sec. cor. of secs. 11 and 12, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Thielsen in 1957

 A fir, 20" dia. bears N.54°E., 30.4 ft with a healed blaze

 A madrone snag, 45" dia., bears S.3°E., 44.2 ft., with no marks visible. (Record, S.1°W.)

and a new bearing tree

 A cedar, 16" dia., bears N.68¾°W., 56.3 ft. mkd. ¼ S11 BT.
Corner is located S.25°E., 1.0 ft. from a wood post at the intersection of barbed and woven wire fences extending N., S.5°E., and W., on a moderate S. slope.