

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records Vol. 15 Page(s) 6526-27)

Set a post, cor. of secs. 1, 2, 11 and 12, from which
A B.Oak 12" dia., bears S.24°E., 44 lks.
A Laurel 8" dia., bears N.46°W., 42 lks
A Laurel 6" dia., bears N.23°E., 62 lks.
A B.Oak 8" dia., bears S.24°W., 80 lks.

J.W. Cole, Nov. 1923 - Vol. 3 Pg. 172 - C.S. File 6/33

Set an Oak post, also a gas pipe 1½" x 36", from which
A W.Oak 12" dia., N.29°W., 263.6 ft.
A W.Oak 9" dia., bears S.22°W., 12.5 ft.
A W.Oak 30" dia., bears S.80°15'E., 225.5 ft.
A Rock ledge marked S.1 CS B.O., N.8°30'E., 283.8 ft.

GLO survey by Hans W.Theilsen, under Group #346, Surveyed, 1957 (DCSO records Vol. 28 Page(s) 12150)

The sec. cor., reestablished by the County Surveyor in 1923 and monumented with an iron pipe, 1½" dia., 8" above ground, firmly set, from which bearing trees and a bearing object marked by the county surveyor:

- A rock ledge bears N.8½°E., 429 lks. dist., mkd. S1 CS BO
- A W.Oak 36" dia., bears S.80¼°E., 342 lks. dist., plainly blazed and healed.
- A W.Oak 12" dia., bears S.22°W., 18 lks. dist., plainly blazed and healed.
- A W.Oak 14" dia., bears N.29°W., 398 lks. dist., plainly blazed and healed.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd:

T29S R7W
S 1 S 1
S 11 S 12
1957

Reset the iron pipe alongside the iron post.

Fd. OK by D. Edwards, April 1999 - M131-44