

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6527)

Set 1/4 sec. post, from which
A B.Oak 18" dia., bears S.69°W., 83 lks.
A W.Oak 10" dia., bears N.33°E., 49 lks.

J. W. Cole, For: Parkinson and Voytilla - November 1923, Vol. 3 Pgs. 171-173, C.S. File 6/33

I set a Fir post, 4" x 4" x 30", from which
A Fir 30" dia., bears N.30°E., 3.0 ft.
A Fir 18" dia., bears S.86°W., 27.5 ft.
(Corner verified by Eppstein in 1927. Vol. 3 Pg. 173)

See survey by Irving in 1950 - C.S. File 44/155

Douglas Co. Surveyors Office - Vernon "Ray" Tracy; Frank Jones; V. Perron - March 6, 1969 - C.S. File 49/139-121

Found - Remains of old fence corner at corner point with only traces of fences N and E.
30" Fir now 38" sawed stump, N.30°E., 3.0 ft. "CSBT" bark scribe in poor condition.
18" Fir now 24" sawed stump, too low, no scribe found, N.86°W., 27.5 ft. (Rec. S.86°W.)
Set Brass cap at cor. mkd: County Surveyor's T 29 S R 7 W
Office, 1969 1/4 S 2 | S 1
New BTs -28" D.Fir N.31°E., 58.5 ft. mkd. "1/4 S1 CSBT".
13" D.Fir N.53°W., 53.1 ft. mkd. "1/4 S2 CSBT".
Corner lies on steep southerly slope, very sparsely covered with D.Fir, and dense brush.

Fd. OK by D. Edwards, April 1999 - M131-43