

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 636400

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Howard Johnstone - For: Roseburg Resources - August 30, 1989  
M 101-60

-----  
Set a 5/8" x 48" Iron rod and alum. cap mkd: "1/4 S24 only".  
New BTs -18" Fir S.72°E., 30.6 ft. scribed "¼ S24 BT"  
17" Cedar S.22°E., 29.0 ft. scribed "¼ S24 BT".

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral  
Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 -  
(DCSO records Vol. 57 Page(s) 22744-5)

-----  
The ¼ sec. cor. of sec. 24 only, established by Johnstone in  
1989, and is accepted as the cor. monumented with an iron rod  
5/8" dia., firmly set, projecting 12" above ground, with an  
aluminum cap (properly) mkd  
from which the remains of bearing trees mkd. by Johnstone  
A sawed fir stump, 20" dia., bears S.76°E., 30.8 ft., with  
illegible scribe marks visible on a partially healed  
blaze.  
A cedar 27" dia. bears S.24¾°E., 29.4 ft. with a healed  
blaze.  
and a new bearing tree  
A fir 8" dia. bears S.44¼°W., 19.4 ft., mkd ¼ S24 BT  
Corner is located on nearly level ground.