

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854) (DCSO records Vol. 15 Page(s) 6526)

Set 1/4 sec. post, at average distance, from which
A Laurel 16" dia., bears N.49°E., 9 lks. dist.
A Laurel 14" dia., bears S.84°W., 15 lks. dist.

GLO resurvey by Hans Theilsen, under Group #346, Surveyed, 1957 - (DCSO records Vol. 28 Page(s) 12149)

Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:

T29S R7W
1/4 S 12
S 13
1957

from which

A Fir 6" dia., bears N.7°E., 110 lks. dist., mkd. 1/4 S12 BT
A Fir 18" dia., bears S.41°W., 106 lks. mkd. 1/4 S13 BT.

GLO resurvey by Hans T. Theilsen, under Special instructions and Group #346 - Surveyed, Aug., 1959 (DCSO records Vol. 30 Page(s) 12806)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:

T29S R7W
1/4 S 12
S 13
1957

from which

A Fir 6" dia., bears N.11°E., 118 lks. mkd. 1/4 S12 BT.
A Fir 14" dia., bears S.20°E., 84 lks. mkd. 1/4 S13 BT.

Douglas Co. Surveyors Office - Stephen J. Flause - John A. Pike - 4/13/1999 - C.S. File 66/8-36

Found - From 1959 GLO resurvey a 2 1/2 inch diameter Brass Cap (marked as below) on a 1 inch o.d. iron pipe firmly set and protruding approximately 12 inches above ground in an East-West fence line (this cap was moved from the position established in the 1957 BLM resurvey). continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

US GENERAL LAND OFFICE SURVEY
T29S R7W
¼ S12
S13
1957

Accessories Found- No evidence of original BTs found.
From 1957 BLM resurvey; found two trees which were probably standing and used in subsequent 1959 BLM resurvey (these trees are described in next entry). Evidence indicates the bearing to 1957 NE BT should be NW.
From 1959 BLM resurvey; two bearing trees found (see above).
A fir 6" diam. now a 21 inch D.B.H. Douglas fir with a fully healed single blaze bears N.11°E., 77.9 feet distant (as per record).
A fir 14" diam. (this size may be in error; location evidence indicates this is the 18" diam. fir from the 1957 BLM resurvey) now a 25 inch D.B.H. Douglas fir with a fully healed single blaze, bears S23½°W, 55.4 feet distant (record S.20°E., 55.4 feet).

New Accessories-

A 6 inch D.B.H. D.Fir double blazed & scribed "¼ S12 CS BT" bears N.35½°E., 16.5 ft. dist.
An 11 inch D.B.H. Incense cedar double blazed & scribed "¼ S13 CS BT" bears S.35°W., 9.6 ft. distant.

Comments- Monument is in an East-West fence line and on an East slope which is the crest of a broad northeast running ridge.

FD. BC & BTs by N. Hibbs, 11/2007 - M154-57