

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 36, 28-7

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854. (DCSO records, Vol. 14 Page 5747)

-----  
Set ¼ sec. post at proper distance, from which  
A B.Oak 30" dia., bears S.27°W., 62 lks. dist.  
A B.Oak 12" dia., bears N.33°E., 48 lks. dist.

H.L. Eppstein, Co. Surveyor - Wit: Harry McCabe; Nichols; Smith - Jan. 25, 1928 - C.S. File 7/45

-----  
This corner was gone and no indication of old BTs, so ran line from SE corner of 36 and 1 to SW corner of 36 and 1 and set quarter corner on line half way between.  
Marked new bearing trees:  
Fir 18" dia., bears N.16°E., 31 ft.  
Fir 16" dia., bears S.47°W., 15 ft.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; Clete Putnam - May 1961 - C.S. File 49/50-58

-----  
Found - 18" now 20" Fir stump, N.     E. 31.0 ft., not N.16°E., shows good bark scribing "BT". (Eppstein)  
16" now 18" Fir stump S.47°W., 15.0 ft. shows old axe work, cut too low, no scribing found.  
Set Brass cap at cor. mkd: County Surveyors ¼ S 36 T28S  
Office, 1961 S 1 T29S R7W  
No trees near for BTs. Angle to large Oak anchor post at fence is S.8½°W., 97.9 ft.

Fd. OK by D. Edwards, April 1999 - M131-43

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-23 A-C

-----  
Found - 2½" brass cap stamped CO SURVEYORS OFFICE dated 1961  
Fence corner post with tag dated 5/61; S.8½°W., 97,1'  
New BT - 9" Fir blazed face and set tag dated 6/26/14; N.71°E., 28.1'