

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 cor. sec. 25 & 30 T29-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6456)

Set 1/4 sec. post, from which:
A Red fir, 5" diam., bears N.15°E., 19 lks.
A Red fir, 8" diam., bears N.35°W., 23 lks.

Re-establishment of corners - Fred Mensch - US Deputy Surveyor - July 1905 (DCSO Vol. 15 Page 6505)

Set an ironstone 16x12x6", 11" in the ground for 1/4 sec. cor. marked 1/4 on W. face, from which:
A Red fir, 12" diam., bears S.60°E., 18 lks., mkd. 1/4 S30 BT.
A Laurel, 24" diam., bears S.78°W., 5 lks., mkd. 1/4 S25 BT.

Ben B. Irving - Deputy Co. Surveyor - Wit. N.E. Richardson, Frank Royer, Robinette, Bill Weightman - May 1934 - M 1-27 & C.S. 37/171

Rock as described in government field notes knocked out. One original B.T. down, other okay. Reset original rock. Remarked O.B.T.
A 14" Fir, S.60°E., 18 lks.
A 36" Fir, S.78°W., 23 lks. New B.T.

James W. Byron - Deputy Co. Surveyor - Dale McFarland and John Powell - Apr. 1962 - C.S. 49/139-34 & C.S. 52/25-12

Found - Stone at cor. & in place as recorded, except we do find + on top & 1/4 mkd: on E. face, not W. face. Both BT's., as recorded by B.B.I., now stumps, down & out of place.

Set Brass cap alongside corner stone & mkd:
County Surveyor's Office

T29S
¼ S25 | S30
R7W | R6W
1962

New BTs -21" R. Fir, bears N.49°E., 71.5 ft. scribed 1/4 S30 CS BT.
8" R. Fir, bears N.29°W., 116.1 ft. scribed 1/4 S25 CS BT.

continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 cor. sec. 25 & 30 T29-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22720)

The ¼ sec. cor. of secs 25 and 30 on the W. bdy of the Tp perpetuated by Irving in 1934, subsequently perpetuated by Byron in 1962 monumented with an iron post, 1¼" dia., firmly set, projecting 13" above ground (lying loose nearby is the fractured original basalt stone 13x9x6" with marks ¼ visible on a face and a cross on top), with brass cap (properly) mkd from which the remains of a bearing tree mkd by Mensch

- A roothole bears S.60°E., 11 .6 ft.
 - and the remains of a bearing tree mkd. by Irving
 - A roothole bears S.80°W., 15.4 ft.
 - and the remains of a bearing tree mkd by Byron
 - A sawed fir stump 31" dia bears N.48¼°E. 70.9 ft., with a healed blaze and axe marks.
 - A fir 28" dia. bears N.30¼°W., 115.8 ft. with a healed blaze
 - and a new bearing tree
 - A fir 6" dia. bears S.87½°E. 51.2 ft. mkd ¼ S30 BT.
- Bury the original stone alongside the iron post.