

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 700339

PRIMARY CORNER DESCRIPTION West 1/4 cor sec. 19 only T29-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6455)

-----  
Set 1/4 sec. post, from which:  
A B Oak, 10" diam., bears S.35°E., 52 lks.  
A Laurel, 18" diam., bears N.49°W., 25 lks.

Howard Johnstone - for Roseburg Resources - Aug. 30 1989  
M 101-60.

-----  
Set 5/8" x 48" iron rod and alum. cap mkd. "1/4 S19 Only".  
New BTs -10" fir, N.24°E., 13 ft. "1/4 S19 BT"  
36" madrone, S.74°E., 3.5 ft. "1/4 S19 BT"

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22723)

-----  
The ¼ sec. cor. of sec. 19 only, on the W. bdy. of the Tp., reestablished by proportionate measurement by Johnstone, in 1989; there is no remaining evidence of the original cor., therefore this position is accepted as the cor., monumented with an iron rod, 5/8" dia., firmly set, projecting 13" above ground, with an aluminum cap (properly) mkd from which bearing trees mkd. by Johnstone  
A fir, 13" dia., bears N.26¾°E., 13.1 ft., with a healed blaze.  
A madrone, 36" dia., bears S.76¼°E., 3.1 ft., with scribe marks 19 T visible on a partially healed blaze.  
Corner is located E.. 2.0 ft. from a broken down woven wire fence extending N. and S., on a gradual E. slope