

PRIMARY CORNER DESCRIPTION Sec. Cor to 13 & 24; 18, 19 of T29-6

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6454 & 6455)

 Set a post, corner of secs. 13,18,19, and 24, from which:
 A chinquapin, 5" diam., bears N.10°E., 10 lks.
 A fir, 18" diam., bears N.5°W., 30 lks.
 A Laurel, 8" diam., bears S.30°E., 20 lks.
 A Laurel, 6" diam., bears S.50°W., 16 lks.

Retracement by Mensch - contract dated 1924 (DCSO records Vol. 14 Pg. 5974)

 The cor. of secs. 13, 18, 19 and 24, on the E. body of the Tp., bears S.88°03'E., 88.03 chs. from the cor. of 13, 14, 23 & 24. This is not the original Ford Cor. and is a fir post, 4" sq., 12" above ground, properly marked; from which:
 A fir, (dead) 5" diam., bears N.49½°E., 26 lks.
 A fir, 14" diam., bears S.15½°E., 26 lks.
 A fir, 16" diam., bears S.44½°W., 27 lks.
 A fir, 7" diam., bears N.52½°W., 12 lks.
 All are correctly and appropriately marked.

BLM Resurvey - Hans W. Thielsen - under group #346 - Apr/May 1957 (DCSO records Vol. 28 Page 12145)

 Corner is determined at record bearing and distance from trees apparently marked but not recorded by Campbell in 1910, accepted and recorded by Mensch in 1924, as follows:

- A sawed fir stump, 28" diam., bears S.15½°E., 26 lks., plainly blazed and healed.
- A fir, 20" diam., bears S.44½°W., 27 lks., marked T29S R7W S24 BT on partly healed blaze.
- A fir, 11" diam., bears N.52°W., 12 lks., marked T29S R7W S13 BT on partly overgrown blaze.

At the corner point

Set an iron post 3' long, 2" diam., 28" in the ground with brass cap marked:

	T29S	
R7W		R6W
S13		S18
S24		S19
	1957	

from which new bearing trees,

- A fir, 21" diam., bears N.45°E., 72 lks., mkd T29S R6W S18 BT.
- A madrone, 17" diam., bears S.82°E., 94 lks., mkd T29S R6W S19 Bt.
- A fir, 8" diam., bears N.47°W., 139 lks., mkd T29S R7W S13 BT.

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Howard Johnstone - for Roseburg Resources - March 6, 1990
C.S. 63/95-3

Found - 1957 Cadastral brass cap and iron pipe.
11" fir, N.52°W., 7.9 ft rotting, open face. 1910 BT
8" now 20" fir, N.47°W. 91.7 ft healed face. 1957 BT
17" madrone, S.82°E., 62 ft. visible scribe. 1957 BT
20" fir, S.44½°W., 17.8 ft rotted open face. 1910 BT
New BTs -6" fir, N.84°E., 12.8 ft.
14" W. fir, S.52°E., 8.2 ft.

Fd. OK, in BLM resurvey by Rogers and Seibold, Cadastral Surveyors, under Group #1517, surveyed April/Aug. 1990 - (DCSO Records, Vol. 50 Pages 19175-76)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22724-5)

The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 13" above ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Campbell
A decayed fir stump, size indeterminate, bears S.15½°E., 17.2 ft., with no marks visible.
A sawed, decayed fir stump, size indeterminate, bears S.44½°W., 17.8 ft. with fragmentary scribe marks visible on an open decayed blaze.
A decayed fir stump, 17" dia., bears N.52°W., 7.9 ft., with scribe marks 13 visible on a partially healed blaze.
and the remains of bearing trees mkd. by Thielsen in 1957
A decayed fir stump, 22" dia., bears N.45°E., 47.5 ft., with no marks visible.
A madrone, 25" dia., bears S.82°E., 62.0 ft., with a healed blaze.
A fir, 25" dia., bears N.47°W., 93.5 ft., with a healed blaze. (Record, 91.7 ft.)
and bearing trees mkd. by Johnstone, in 1989
A fir, 11" dia bears N.81½°E., 13.9 ft with a healed blaze
A fir, 14" dia., bears S.53°W., 7.9 ft with a healed blaze
Corner is located S.20°E., 4.7 ft. from a wood post at the intersection of barbed and woven wire fences extending N.2°W. and N.88°W.