

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 042010

PRIMARY CORNER DESCRIPTION NE Cor. A. Martindale DLC #42

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856 - DLC Volume Page 585

-----  
Set a post, from which  
A Pine 18" dia., bears S.85°W.

Ben B. Irving, Deputy Co. Surveyor - Wit: W.S. Crear; C. McCann; Wm. M. Porter - Dec. 1927 - C.S. File 7/38; M 1-63; Vol. 3 Pg. 281

-----  
Identified by old rock used as corner for many years. This rock is in South edge of county road.

New BTs:

A 14" W.Oak S.62°W., 81 lks. scribed Cl. 42 CS BT.

A 20" Fir N.76 3/4°E., 433 lks. scribed.

Reburied this rock and filled hole with gravel.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 9, 1970 - C.S. File 54/38-29

-----  
Found - Did not find rock used for corner, did not dig up pavement.

14" now 26" W.Oak S.62°W., 53.5 ft., shows good scars.

20" now 38" D.Fir N.76 3/4°E., 285.8 ft., shows good BT scar and faint bark scribe.

Set 5/8" I. Rod flush with road surface, on South edge of road at corner point. (See Northcraft's corner on M 42-13)

Reblazed and rescribed:

38" D.Fir N.76 3/4°E., 285.8 ft. mkd. "NE DLC 42 CS BT".

Fd. OK, Sept. 2, 1986 by Oregon State Hwy Dept. - C.S. File 63/9-26

Douglas Co. Surveyor's Office - Crew: Stephen Flause & Jeff Lorsung - 9/25/2018 - C.S. File 67/45-9

-----  
Found - A bent 5/8" iron rod by John M. Powell in 1970 firmly set, buried 0.6 ft. under the asphalt at the intersection of Main Camas Road & South Camas Rd I referenced and removed the bent iron rod and replaced it with 5/8"x30" iron rod, buried 0.8 ft. under the pavement with a 1 1/2" yellow plastic cap marked as follows: DOUG. CO • SURVEYOR  
I backfilled the excavation with asphalt cold patch and set a 12" ginnie & tack directly over the 5/8" iron rod. continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 042010

PRIMARY CORNER DESCRIPTION NE Cor. A. Martindale DLC #42

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Found continued -

BTs BB Irving in 1927 per M 1-63:

A 47" D. Fir bears, N.76¼°E., 285 8 ft. with healed blaze. (Rec. N.76¾°E.)

A 36" W. Oak bears, S.61½°W., 53.5 ft. with healed blaze (Rec. S.62°W.)

A Reference Monument by J. Byron in 1961 per M 20-18:

A ¾" iron rod bears N.85°37'18"W., 287.43 ft.

New - A 20" W.Oak bears, S.15°W, 45.1 ft. scribed "NE DLC 42", "CSBT" on a double blaze

Note - Basis of Bearings M 42-13

All BTs have BT tags attached.

All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to a 2" PK nailed into the side and center of the root crown.

The corner is located 1 ft. from the South edge of Main Camas Road.

Compass decl. 15°E.