

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 043020

PRIMARY CORNER DESCRIPTION NW Cor. Geo. Day DLC #43

Alias 044010 Description NE Cor. Wm. Day DLC #44

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856 - DLC Volume, Page 587 and 589

Set a post Quadrangular trench with stone in center.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #584 - Surveyed July 1965 - (DCSO records Vol. 33 Page(s) 13886)

The point for the NE. cor. of the Wm. P. Day DLC #44, determined at the intersection of fences extending S., E., and W. This point is accepted as the best available evidence of the original corner, and is used by local land owners.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 23" in the ground, with brass cap mkd:

	DLC	42
DLC		DLC
44		43
		1965

from which

An Ash 35" dia., bears N.43 $\frac{1}{4}$ °E., 101 lks. dist. mkd. DLC 42 BT.

An Ash 9" dia., bears S.19°W., 102 lks. dist. mkd. DLC 44 BT.

No other suitable trees available within limits.

Fd. OK, Sept. 26, 1986 by OSHD - C.S. File 63/9-37