

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 043030

PRIMARY CORNER DESCRIPTION SW cor. Geo. Day DLC #43

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856 - DLC volume, Page 587

Set a post, from which
A Fir 12" dia., bears N.87°E., 10 lks.

J.W. Cole, Surveyor - Wit: N.E. Richardson; J.B. Stobie - April 25, 1923 - Vol. 3 Pg. 148-149

This corner was renewed from line trees called for in govt. field notes, East of the corner and on the South bdy. of Claim. I set an Iron pipe 1¼" x 36" from which
A Maple 12" dia., N.00°20'W., 55.4 ft.
A Maple 10" dia., N.32°15'E., 73.5 ft.
No evidence of bearing tree found.

Fd. OK Nov. 1989 by Laney - M 109-20

Kris DeGroot - For: Silver Butte Timber - 9/2007 - M 146-63

Found - 3/4" galvanized steel pipe by Laney in 1989 per M109-20, firmly set, projecting 2" above the ground, with a aluminum cap stamped;
GEORGE E LANEY
LS 1623
And a monument per m109-20:
A 1" iron pipe w/1½" aluminum cap per M109-20, which bears S..0°6'58"W., 50.15 ft., projecting 15" above ground.
And a new bearing tree:
A 10" D.Fir bears S.64°30'W., 28.2 ft. Scribed "SW DLC 43"