

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 043040

PRIMARY CORNER DESCRIPTION SE Cor. Geo. Day DLC #43

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856 - DLC Volume, Page 587

-----  
Set post from which  
A W.Oak 8" dia., bears N.11°W., 59 lks.

J. W. Cole, Deputy Co. Surveyor - Wit: N.E. Richardson; J.B. Stobie - April 1923 - Vol. 3 Pgs. 148-49

-----  
This corner was renewed from the original BT, a W.Oak 14" dia., N.11°W., 59 lks. Tree had been opened previously and scribe marks had rotted off. Line trees called for in the govt. field notes both North and West at proper distances. I set an Iron Pipe 1¼" x 36", from which  
A Fir 40" dia., bears S.50°E., 26.7 ft.  
A Fir 48" dia., bears N.43°30'E., 69.9 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Oct. 1958 - C.S. File 49/100-47

-----  
Found - 1¼" Iron pipe at fence corner.  
Orig. now 20" W.Oak, N.11°W., 38.9 ft., shows old scar, rotted face, checks bearing and distance. Both stumps of BTs recorded by Cole, 1923, no scribing found, bearing recorded N.43½°E. should be N.38½°E. Other bearing to SE. BT OK, Both distances check.  
I do not set brass cap at corner.  
New BTs- 6" W.Oak bears S.30°W., 37.3 ft. scribed SE Cl. 43 CS BT.  
Rescribe orig. now 20" W.Oak N.11°W., 39.9 ft., scribed S.E. CL. 43 CS BT.

Fd. 10" Yew post, March 1990 - Partition plat 1990-0028

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 12/14/1999 - C.S. File 66/13-7

-----  
Found - 1¼" iron pipe 1" below ground at fence corner.  
OBT now gone.  
40" now 36" dia., 3 ft. high D.Fir stump no scribing found bears S.50°E., 29. 3 ft. (rec. S.50°E., 26.7) 1923  
48" now 44" dia., 3 ft. high D.Fir stump no scribing found bears N.35°E., 71.3 ft. (rec. N.38½°E., 69.9) 1923  
Our dist's on 1923 BTs take to center  
continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 043040

PRIMARY CORNER DESCRIPTION SE Cor. Geo. Day DLC #43

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

6" now 8" dia., W.Oak no blaze visible bears S.30°W., 37.3 ft. (agrees w/rec) 1958  
New BTs- 8" dia., double trunked W.Oak double blazed & scribed on West trunk "SE DLC 43 CS BT" center of root crown bears N.48½°E., 101.7 ft.  
28" dia., D.Fir double blazed & scribed "SE DLC 43 CS BT" bears S.76°W., 27.3 ft.  
Fence lines run north & west of corner. IP along NW edge of fence post (yew)