

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 045010

PRIMARY CORNER DESCRIPTION NW Cor. H.O. Waters DLC #45

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856 - DLC Volume, Page 575

Set a post from which
A Yellow Pine 30" dia., bears S.30°E., 274 lks.

(Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 5983-84)

The point for NW. cor. of Claim No. 45, located by measurement from the original bearing trees.
At the exact cor. point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for cor. No 2 of DLC #45, with brass cap mkd: T29SR8W
S1:AP 2
:DLC 45
1924
from which
stump of original bearing tree bears S.30°E., 274 lks.
New BTs- A Pine 12" dia., bears S.7°E., 96 lks. dist. mkd. AP 2 DLC 45 BT.
A B.Oak 8" dia., bears S.69°E., 95 lks. mkd. AP 2 DLC 45 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 29, 1966 - C.S. File 54/38-11

Found - GLO brass cap, 1924, properly marked.
8" now 15" B.Oak S.69°E., 62.7 ft., opened for scribe "5"
12" Pine, no trace of this BT.
New BT - 17" B.Oak N.48°E., 29.4 ft. mkd. NW DLC 45 CS BT.
Reblazed and rescribed:
15" B.Oak S.69°E., 62.7 ft. mkd. NW DLC 45 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/14/1999 - C.S. File 66/12-10

Found - 2½" dia., brass cap on a 1" O.D. iron pipe, protrudes 7" above ground.
8" now 20" dia., 1½ ft. high B.Oak stump, with good scribing visible "AP 24" bears S.69°E., 62.7 ft. (agrees w/rec.) 1924
No other BTs found.
New BTs- Double trunk Madrone double blazed scribed "NW DLC 45 CS BT" on 9" dia., Westerly trunk, base Westerly trunk bears S.15½°E., 34.7 ft.
continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 045010

PRIMARY CORNER DESCRIPTION NW Cor. H.O. Waters DLC #45

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

17" dia., W.Oak double blazed and scribed "NW DLC 45 CS BT" bears S.84°E., 43.3 ft.
Note - Corner lies along the southerly edge of a power line clearing that runs E-W and at the intersection of fence lines running East & South.