

PRIMARY CORNER DESCRIPTION SW Cor. H.O. Waters DLC #45

Alias	Description
Alias	Description
Alias	Description
Alias	Description

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856 - DLC Volume Page 575

Set a post from which
A Yellow Pine 14" dia., bears N.30°E., 62 lks.

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 5984)

The SW. cor. No 3 of Claim No. 45, which is a 3" Iron pipe 18" above ground, alongside a sandstone, 10x8x3 ins., above ground, from which
A Yellow Pine, original BT, 24" dia., bears N.28½°E., 62 lks. dist., not N.30°E., marks plain.
I mark
A Fir 40" dia., bears N.76°E., 71 lks. dist. mkd. AP 3 DLC 45 BT.

Floyd C. Frear; Arthur Boyer - June 1957 - M 5-45

Renewed from original BT. (Pine)
Set a 2½" x 4 ft. Iron pipe and rock at corner., from which
A 7" R.Fir S.86°W., 15.4 ft.
A 5" W.Fir S.82°E., 21.7 ft.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 28, 1966 - C.S. File 54/38-10

Found - 2½" I.Pipe and stone at DLC corner.
Orig. 24" Pine, now stump, N.28½°E., 40.9 ft., tree opened.
Orig. 40" Fir, now stump, N.76°E., 46.9 ft., shows good scar.
7" now 11" D.Fir S.86°W., 15.4 ft., bark scribed "C BT" visible.
5" now 11" W.Fir S.82°E., 21.7 ft., shows good scar.
Reblazed and rescribed:
11" D.Fir S.86°W., 15.4 ft. mkd. "SW DLC 45 CS BT"

Fd. OK, 1978 by OSHD - See M-3

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/13/1999 - C.S. File 66/12-8

Found - 2½" O.D. iron pipe protrudes 20" above ground.
9"x3" protrudes 6" above ground stone is south of BC/IP 0.7 ft. continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 045020

PRIMARY CORNER DESCRIPTION SW Cor. H.O. Waters DLC #45

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

14" Pine now good root hole bears N.28½°E., 40.9 ft.
(agrees w/rec.) OBT

40" now 48" dia., 1½ ft. high D.Fir stump scribing
found "45 BT" bears N.73½°E., 46.9 ft. (Rec.
N.76°E., 46.9 ft) 1923

5" now 18" dia., 1 ft. high rotted D.Fir stump, with
illegible scribing, bears S.78½°E., 21.7 ft.
(rec. S82°E., 21.7 ft.) 1957

7" now 15" dia., D.Fir with a fully healed double
blaze bears N.89°W., 15.4 ft. (Rec. S.86°W., 15.4
ft.) 1957

New BTs- 4" D.Fir double blazed & scribed "X BT" bears
N.51½°E., 13.1 ft.

7" W.Oak double blazed & scribed "SW DLC 45 CS BT"
bears S.13°W., 16.7 ft.

Note - Corner lies at the intersection of a fence corner
with fence line running North & East.