

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (SW Tsp. Cor)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6575)

Marked a Sugar Pine 20" dia. for cor. of Tps. 29 and 30 S., Rgs. 8 and 9 W., from which
A Sugar Pine 30" dia., bears N.80°E., 5 lks. dist.
A Fir 10" dia., bears S.88°W., 28 lks. dist.
A Fir 10" dia., bears N.50°W., 73 ks. dist.
A Laurel 12" dia., bears S.10°E., 70 lks. dist.

Note: On pages 6613-14, Byars describes finding a corner, describes BTs that do not match Hathorn's or any new information. I could find nothing else prior or after that matches. DID NOT TYPE. V. Laugen, March 1997

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - July 17, 1958 - C.S. File 49/100-6

Found - Sugar Pine tree, now 45" at Tsp. Corner.
Sugar Pine now 45", N.80°E., 3.3 ft.
D.Fir now 25" dia., S.88°W, 18.5 ft. Cut into this tree to expose part of upper blaze. Find good scribing "W" and "S 36".
Fir stump now 40" dia., N.50°W., 48.2 ft. Opened lower scar but found only charred face.
Remains of badly rotted Laurel stump, S.10°E., 46.2 ft.

Set Brass cap 10 ft. North of true corner for Witness Corner, mkd: "County Surveyors Office 1958 W.C. 10 ft. South T29S R9W S36 S1 S31 S6 R8W T30S."

Blaze and scribe:
16" D.Fir S.49½°W., 27.5 ft. mkd. T30S R9W W.C. S1 CS BT.
24" D.Fir N.60°W., 32.6 ft. mkd. T29S R9W W.C. S36 CS BT.
45" S.Pine (N.E. BT for true cor.) S.25°E., 10.0 ft. mkd. T30S R8W W.C. S6 CS BT.
19" W.Fir N.73°E., 33.4 ft. mkd. T29S R8W W.C. S31 CS BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #584 - Surveyed July 1965 - (DCSO records Vol. 33 Page(s) 13880)

(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (SW Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The Tps. corner, perpetuated and recorded by Byron in 1958, the corner point is occupied by the original corner tree, a Sugar Pine 45" dia., mkd. with healed blazes on the NE. and SE. sides, from which the remains of the original bearing trees:

A Sugar Pine 45" dia., bears N.80°E., 5 lks. dist., no original marks remaining. Remarkd T30S R8W WC S6 CS BT on a double blaze by Byron.

A Fir 27" dia., bears S.88°W., 28 lks. dist. mkd. W S36 on an open blaze.

A sawed Fir stump 36" dia., bears N.50°W., 73 lks. dist. with no marks remaining.

and bearing trees and iron post mkd. by Byron

A Fir 21" dia., bears N.57°E., 58 lks. dist. mkd. with a healed double blaze.

A Fir 18" dia., bears S.66°W., 34 lks. dist. mkd. with a partially healed blaze.

A Fir 27" dia., bears N.49¼°W., 59 lks. dist., mkd. with a partially healed double blaze.

An Iron post 1½" dia., firmly set, 16" above the ground with brass cap mkd. County Surveyors Office T29S WC T30S R9W R8W S1 S6 S21 S36 Cor. 10 ft. S 1958, bears North 15 lks. dist.

Add a reference monument:

An Iron post 28" long, 2½" dia., set 22" in the ground for a reference monument, bears S.35°E., 18½ lks. dist., with brass cap mkd. RM T30S R8W S6 1965 and an arrow pointing to the corner.

Found OK by M. Smalley, August 2002 - M137-50