

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; & S. 12, T29-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6573)

-----  
Set ¼ sec. post, from which  
A Fir 12" dia., bears S.64°W., 31 lks. dist.  
A Fir 10" dia., bears S.15°E., 19 lks. dist.

H.L. Eppstein - Wit: W.S. Crer; C.S. Wiley; W.G. Reetz - 1922  
- C.S. File 4/70

-----  
Set rifle barrel for corner from one old BT. Cut down but BT scribe marks plain. Marked new BTs:  
Red Fir 20" dia., S.65°W., 71.5 ft.  
Red Fir 24" dia., S.20°E., 61.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Sept. 1958 - C.S. File 49/100-16

-----  
Found - 20" now 30" Fir stump, S.65°W., 71.5 ft., shows scribing "C".  
24" now 30" Fir stump S.20°E., shows scribing "T".  
I do not find rifle barrel set for corner in 1922.  
Set ¾" Iron rod at corner and 3" under road surface.  
New BTs- 15" Cedar bears S.32°E., 68.3 ft. scribed ¼ S7 CS BT  
8" R.Fir bears S.72°W., 63.0 ft. scribed ¼ S12 CS BT

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15752-53)

-----  
The ¼ sec. cor., perpetuated and recorded by Irving in 1927, from original evidence no longer in existence, subsequently perpetuated and recorded by Byron in 1958, determined from the remains of bearing trees mkd. by Irving  
A sawed Fir stump 30" dia., bears S.65°W., 109 lks. dist. with scribe mark B visible on opened blaze.  
and bearing trees mkd. by Byron:  
A Cedar 15" dia., bears S.32°E., 104½ lks. dist., with scribe marks ¼ S7 CS BT visible on partially healed double blaze.  
A Fir 8" dia., bears S.72°W., 95½ lks. dist., with healed blaze.  
At the corner point  
Seat a brass tablet ¾" dia., 3½" stem, in drill hole, flush with surface of pavement with top mkd. (Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; & S. 12, T29-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 29 S  
R 9 W R 8 W  
<sup>1/4</sup>  
S 12 | S 7  
1973

Corner is located in middle of pave road, 30 lks. wide, bears  
N.70°W. and S.70°E.

Fd. Ok by Greg Lang - 12/1998 - M 131-10  
Fd. BC & 2 BTs, by Bartt Heichel 4/2025 - M184-77 A-B