

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T29-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6572-73)

Set post, cor. secs. 6, 7, 1 and 12, from which
A Fir 18" dia., bears N.75°E., 5 lks. dist.
A Fir 12" dia., bears S.67°W., 61 lks. dist.
A Laurel 9" dia., bears S.32°E., 52 lks. dist.
A Laurel 9" dia., bears N.58°W., 50 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Sept. 1958 - C.S. File 49/100-10

Found - Orig. 18" now 40" R.Fir, N.75°E., 3.3 ft., shows old bark.

Orig. 12" now 30" Fir stump, S.67°W., 40.2 ft., shows old bark scribing "T29S R9W". Also shows newer bark scribing.

Stump hole that checks bearing & distance for SE BT.
No trace of NW. BT.

Find 3" x 6" x 12" sandstone at corner.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S
R9W S 1 | S 6 R8W
S 12 | S 7
1958

New BTs- 12" R.Fir bears N.42°W., 59.2 ft scribed S1 T29S R9W
CS BT.

16" R.Fir bears S.59½°W., 44.5 ft. scribed S12 T29S
R9W CS BT.

Rebark scribe 40" R.Fir N.75°E., 4.2 ft. S6 T29S R8W
CS BT.

14" R.Fir bears S.28°E., 42.7 ft. scribed S7 T29S
R8W CS BT.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14002-03)

The Sec. cor., perpetuated and recorded by Byron in 1958, monumented with an iron pipe 1" dia., firmly set, extending 8" above ground with brass cap mkd. in 1958, from which he remaining original bearing trees:

A Fir 38" dia., bears N.75°E., 6 lks. dist. with scribe marks T29S R8W visible on old bark blaze and with healed blaze at base. This tree has been remarked T29S R8W S6 CS BT on bark blaze. (Rec. 5 lks.)

(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T29-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed Fir stump 25" dia., bears S.67°W., 61 lks. dist., with illegible scribe marks visible on old bark blaze and with healed blaze at base. This tree has been remarked T29S R9W S12 on bark blaze.
and bearing trees mkd. by Byron:
A Fir 23" dia., bears S.30°E., 64 lks. dist. with healed double blaze.
A Fir 18" dia., bears S.57°W., 68 lks. dist., with healed double blaze.
A Fir 14" dia., bears N.42°W., 89½ lks. dist. with healed double blaze.
Add marks BLM 1966 to brass cap.

Fd. and used in BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15753-54)

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024 - M185-27

Found - A 2½" BLM brass cap on a 1" diam iron post 0.5' above ground.
A Fir 40" diam bears N.75°E. 3.3' (5 lks.) With healed blaze and loc poster on N. face.
A Fir 32" diam bears S.30°E. 42.7' to a nail at the right side center with a healed blaze at the loc poster on W. face.
A Fir 25" diam bears S.57°W. 44.5' to a nail right side center with a healed blaze and loc poster on N.W. face.
A Fir 18" diam bears N.42°W. 59.2' dist to a nail at left side center with healed blaze and loc poster on rev.
New - A Fir stump 23" diam 6' bears S.67°W. 40.3' (61 lks) Added paint, blazes, nails (per above locations), and tags to rev and face of Bts.

Fd. BC & 5 BTs, by Bartt Heichel 4/2025 - M184-77 A-B