

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6601)

Set ¼ sec. post, from which
 An Oak 24" dia., bears N.42°W., 106 lks. dist.
 An Oak 20" dia., bears S.11°W., 42 lks. dist.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #584 - Surveyed July 1965 - (DCSO records Vol. 33 Page(s) 13886-87)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
 T 29 S R 8 W
 ¼ S 30
 S 31
 1965

from which
 A Fir 14" dia., bears N.14½°E., 65 lks. mkd. ¼ S30 BT.
 An Oak 9" dia., bears S.45½°W., 109 lks. mkd. ¼ S31 BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 10/15/1998 - C.S. File 66/4-5

Found - 3¼" dia., brass cap on a 2½" O.D. iron pipe, protrudes 3" above ground, properly marked. 1965
14" now 30" dia., D.Fir with a fully healed blaze bears N.14½°E., 42.9 ft. (agrees with rec.) 1965
9" now 13" dia., W.Oak with a fully healed blaze bears S.45½°W., 71.9 ft. (Agrees with rec.) 1965
New BTs- 11" dia., W.Oak, double blazed and scribed "¼ S31 CS BT" bears S.57½°E., 11.7 ft.
8" dia., D.Fir, double blazed and scribed "¼ S30 CS BT" bears N.1°E., 20.6 ft.

Fd. IP w/BC - James M. Standley - For: ODOT - 12/2007 - St. Hwy 42-013A