

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 140540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15775)

Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line.

Set an iron post 28" long, 2½" dia., 22" in the ground with brass cap mkd: C ¼ S 7
1973

from which

A Fir 19" dia., bears N.42½°E., 198 lks. dist. mkd. C ¼ S7 BT.

A Cedar 8" dia., bears N.11½°W., 34 lks. dist. mkd. C ¼ S7 BT.

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024

Found - A 3¼" BLM Brass cap. A 2½" Iron post 0.3' above ground.

A Cedar 27" diam bears N.11½°W. 22.44' with healed blaze and tag by Akin 8/73.

A Fir 8" diam bears N.30°E. 30.15' to a nail scribed "C¼S7BT" with LS washer and tag 90216 10/24.

A Fir 15" diam bears S.69¾°E. 20.05' to a nail scribed "C¼S7BT" with LS washer and tag 90216 10/24.

A Fir 24" diam bears S.55°W. 22.45' to a nail scribed "XBT" with LS washer and tag 90216 10/24.

New - Added post W. 5' and N. 5' with boundary signs.