

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6607)

-----  
Set ¼ sec. post, from which  
A Cedar 12" dia., bears S.20°W., 18 lks. dist.  
A Fir 12" dia., bears N.75°E., 7 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - Jan. 24, 1963 - C.S. File 49/139-99

-----  
Found - 34" Cedar stump S.20°W., 11.9 ft., shows good scar and burl wood about right size and shape for BT scar and faces in right direction, however, center is rotted away, no scribing left.  
No trace of other orig. BTs.  
30" Yew N.3°W. 8.5 ft. with scribing "¼ S6 BT CC"  
Corner position also fits old tie in govt. notes to Middle Fork Coquille River.

Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R 8 W  
¼  $\frac{S\ 6}{S\ 7}$   
1963

New BTs- 15" D.Fir S.16°W., 29.8 ft. mkd. ¼ S7 CS BT.  
11" W.Fir N.27°W., 22.2 ft. mkd. ¼ S6 CS BT.

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15773-74)

-----  
The ¼ sec. cor., perpetuated and recorded by Godfrey in 1963, from original evidence no longer in existence, monumented with an iron pipe 1" dia, firmly set projecting 6" above ground, with brass cap mkd. in 1963  
from which bearing trees mkd. by Godfrey  
A Fir snag 12" dia., bears N.27°W., 37½ lks. dist., with healed double blaze.  
A Fir 20" dia., bears S.16°W., 44 lks. dist., with healed double blaze.  
and a bearing tree of no record  
A Yew 28" dia., bears N.3°W., 14 lks. dist., with scribe marks ¼ S6 BT visible on partially healed double blaze.

continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Fd. OK by G. Lang, Feb. 2000 - M134-30

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates  
Professional Land Surveyors - 2024

-----  
Found - A 2½" Brass cap on 1" Iron pipe 0.5' above ground  
with a post E. 0.4'.  
A Fir 42" diam bears S.16°W. 29.0' to a nail left  
side center, with a healed blaze.  
A Yew 35" diam bears N.3°W. 9.2' to a nail right  
side center, with partially visible scribe in  
open face and tag by "VIN 1-11-63"  
New - Add paint, blazes, nails (per above locations),  
and tags to face and rev of Bts.  
Add post South 6' and West 6'.