

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6601)

-----  
Set ¼ sec. post, from which  
    An Oak 18" dia., bears S.52°E., 689 lks. dist.  
    An Oak 24" dia., bears S.4¼°W., 689 lks. dist.  
Geo. Day's house bears S.84°E., about 10 chs.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Nov. 21, 1989 - C.S. File 64/3-12

-----  
Looked for, not found.  
We opened 24" Oak with hole, as requested by George Laney.  
Axe marks found appear to be made by a previous search of tree. No scribing or blazes found.

BLM Dependent resurvey by Timothy J. Moore & A. Bert Skeesick, Cadastral Surveyors under Group #2097, surveyed Sept. 2004 (DCSO rec. Vol. 55 pg(s) 21285)

-----  
Point for the ¼ sec. cor. of secs. 29 and 30 at proportionate dist.; there is no remaining evidence of the original cor. Corner location falls in cultivated pasture; **no monument was set at landowners' request.**