

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6601-02)

Set post cor. secs. 19, 20, 29 and 30, from which
An Oak 24" dia., bears S.1°W., 1478 lks. dist.
An Oak 24" dia., bears S.2°E., 1503 lks. dist.
An Oak 40" dia., bears N.40°E., 1329 lks. dist.
An Ash 15" dia., bears N.26°W., 2900 lks. dist.

Jesse W. Cole, Co. Surveyor - Wit: N.E. Richardson; Mr. Nicewood - April 23, 1923 - Vol. 3 Page 148

Corner of secs. 19, 20, 29, & 30 which I renewed from old BT alive and standing bearing faint scribe marks.
Set Iron pipe 1¼" x 36", 16" below surface of ground, from which
Pine tree 24" dia. (in SE. corner of Cemetery), N.32°E., 537.0 ft.
A Pear tree, 10" dia., N.31°30'W., 164.6 ft.
A Fir tree, 20" dia., S.41°45'E., 730.0 ft.
an Iron pipe 1¼" x 40", N.89°07'E., 453.0 ft. on section line and west bdy. of highway to Coast.

Found I.P., Dec. 1984 by E. Bloom - M 98-14
Found OK, Sept. 1986 by OSHD - C.S. File 63/9-24
Fd. OK, Dec. 1992 by G. Lang - M 117-45

BLM Dependent resurvey by Timothy J. Moore & A. Bert Skeesick, Cadastral Surveyors under Group #2097, surveyed Sept. 2004 (DCSO rec. Vol. 55 pg(s) 21285-6)

The cor. of secs. 19, 20, 29, & 30, perpetuated by the Douglas County Surveyor's Office, in 1923, monumented with an iron pipe, 1½" dia., firmly set, projecting 2" above ground, from which the remains of an original bearing tree
A sawed decayed stump, size and species indeterminate, bears N.40½°E., 872.1 ft., with no marks visible.
(Record, N.40°E., 877.1 ft.)
and bearing trees mkd. by the Douglas County Surveyor's Office
A pine, 45" dia., bears N.32°E., 538.3 ft., with a healed blaze.
A fir, 28" dia., bears S.36¾°E., 685.6 ft., with a healed blaze.
At the corner point in the center of the iron pipe.
continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Drive an aluminum rod, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground (driving the iron pipe below ground surface), with aluminum cap mkd.

T29S R8W
S 19 | S 20
S 30 | S 29
2004

Corner falls at intersection of fences extending East, South, and West.

Fd. BC by D. Edwards, 8/2011 - M162-80