

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6603)

-----

Set ¼ sec. post, from which  
    An Oak 20" dia., bears S.38°E., 1275 lks. dist.  
    An Oak 20" dia., bears S.59°E., 1275 lks. dist.  
No trees convenient on W. side of the line.

Ben B. Irving - Deputy Co. Surveyor - Wit: W.S. Crear; C. McCann; Wm. M. Porter - Jan. 4, 1928 - Vol. 3 Pg. 280; M 1-63

-----

Set by single proportional measurement along the West line of section 20.  
Set sandstone 4" x 6" x 14" chiseled X on top and ¼ on East face 14" under ground for corner.  
    A 14" Fir S.18°45'W., 913 lks. scribed ¼ S19 CS BT.  
    A 16" Fir S.1°1'E., 865 lks. scribed ¼ S20 CS BT.