

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6603)

-----  
Set post cor. secs. 17, 18, 19 and 20.  
Deposited charred stake, and raised mound with trench as per instructions.

Ben B. Irving, Deputy Co. Surveyor - Wit: W.S. Crear; C. McCann; Wm. M. Porter - Jan. 4, 1928 - Vol. 3 Pg. 290; M 1-63

-----  
Set by double proportionate distances from ¼ section corners, N., E., and W. and section corner S.  
Set a sandstone 4" x 6" x 20"., 12" underground for corner, 10 ft. West from creek bank, chisled X on top and 5 notches on E. face, 1 notch on W. face, 3 notches on N. face, 3 notches on S. face, from which  
A 20" Ash N.18°33'W., 1112 lks., scribed T29S R8W S18 CS BT.  
A 14" Fir S.52°6'E., 935 lks., scribed T29S R8W S20 CS BT  
No other tree within reasonable distance in proper quadrants.  
Peak of Signal Tree Lookout house on Kenyon Mtn. is S.61°22'W.  
Lookout Tree on Kenyon Mt. is S.61°25'W.  
Group of high trees on top of Ketchum Mt. is S.33°3'W.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell, crew - For: Douglas Co. Health Dept. - April 6, 1962 - C.S. File 52/114; RM 2-20

-----  
Found - Stone with + on top, 12" under and 10 ft. West of creek bank.  
Also find now 22" Fir 617.1 ft. Shows old scars.  
We find now 24" Ash stump, N.7½°W., 733.9 ft., (not N.18°33'W.) shows old scribing.  
Set brass cap alongside stone mkd: County Surveyors Office  
T 29 S R 8 W  
S 18 S 17  
S 19 S 20  
1962  
New BTs- 14" Ash N.9°30'E., 30.3 ft. scribed S17 T29S R8W CS BT.  
9" Ash S.18°E., 30.0 ft. scribed S20 CS BT.  
No other BTs near.