

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6604)

Set post cor. secs. 7, 8, 17 and 18, from which
An Ash 12" dia., bears S.75°W., 9 lks. dist.
An Ash 10" dia., bears N.10°E., 27 lks. dist.
A Maple 18" dia., bears N.30°W., 48 lks. dist.
A Maple 24" dia., bears S.40°E., 71 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell, crew - For: Doug. Co. Health Dept. - April 6, 1962 - C.S. File 52/114; RM 2-20

By double proportion.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 8 W
S 7 S 8
S 18 S 17
1962

New BTs- 12" Myrtle bears S.64°E., 12.9 ft. scribed S17 T29S R8W CS BT.
30" Maple bears N.79°W., 39.0 ft. scribed S7 T29S R8W CS BT.
11" R.Fir bears N.43°E., 121.0 ft. scribed S8 T29S R8W CS BT.
6" Myrtle bears S.51°30'W., 43.0 ft. scribed S18 CS BT.

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15769)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd: T 29 S R 8 W
S 7 S 8
S 18 S 17
1973

from which bearing trees mkd. by Byron in 1962
A Fir 12" dia., bears N.46½°E., 205 lks. dist., with healed double blaze.
A Myrtle 12" dia., bears S.83°E., 46 lks. dist., with scribe marks T29S R8W S17 BT.

(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Myrtle 8" dia., bears S.28°W., 51 lks. dist., with scribe marks S18 CS BT visible on partially healed double blaze.

A Maple 31" dia., bears N.72°W., 34½ lks. dist., with scribe marks T29S R8W S7 BT visible on partially healed double blaze.

and a new bearing tree

A Fir 10" dia., bears S.50°W., 30 lks. dist., mkd. T29S R8W S18 BT.

From this point, a local corner established by Byron bears S.73°29'E., 0.28 chs. dist., monumented with an iron pipe 1" dia., firmly set, projecting 8" above ground, with brass cap mkd. T29S R8W S7 S8 S17 S18 1962.

Survey by Mark Smalley - For: Roseburg Resources and Ninette West - Aug. 1995 - M 119-69

Found - 1973 Cadastral brass cap/iron pipe.
40" Maple N.72°W., 22.8 ft., healed.
14" Myrtle S.83°E., 30.4 ft., scribe visible.
8" Myrtle S.28°W., 33.7 ft., scribe visible.
18" Fir S.50°W., 19.8 ft., healed.
1962 County BC/IP, bears S.73°29'E., 18.5 ft.
New BT - 9" Cedar N.61°E., 11.8 ft. "S 8 BT".

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Aug. 1997 - C.S. File 64/79-9

Cut off DCSO brass cap - corner found ok.