

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6606)

Set 1/4 sec. post, from which
A W.Oak 18" dia., bears N.44°W., 45 lks. dist.
A W.Oak 40" dia., bears S.60°E., 59 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell, crew - For: Doug. Co. Health Dept. - April 6, 1962 - C.S. File 52/114; RM 2-20

Found - Orig. 40" now 44" W.Oak, S.60°E., 38.9 ft., shows old axe work, face rotted. No scribing found.
Orig. NW. BT, not found.
Corner lies in field. SET Witness Corner.
Set 3/4" iron rod at 1/4 cor., 8" under.
B.C. at wit. cor. mkd. "21" West to 1/4 S 7 S 8 T29S R8W"
New BTs- 17" R.Fir bears S.44°E., 9.7 ft. scribed WC 1/4 S8 CS
BT
33" W.Oak bears S.39°W., 95.0 ft. scribed WC 1/4 S8 CS
BT.

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15773)

The 1/4 sec. cor. perpetuated and recorded by Byron in 1962, from original evidence no longer in existence, monumented with an iron rod, 3/4" dia., with top 8" below surface of ground.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 30" in the ground, directly over iron rod, with top 2" below surface and brass cap mkd:
T 29 S R 8 W
1/4
S 7 S 8
1973
from which
An Iron post 28" long 2 1/2" dia., set 24" in the ground, for a reference monument, bears N.42 1/4°E., 48 lks. dist., with brass cap mkd. T29S R8W S8 RM 1973 and an arrow pointing to the corner.

From this corner, a point established by Byron for a witness (Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

corner, bears East, 0.30 chs. dist., monumented with an iron post, 1" dia., firmly set, projecting 8" above ground with brass cap mkd. as in 1962, from which bearing trees mkd. by Byron:

A Fir 28" dia., bears S.48°E., 14 lks. dist., with healed double blaze.

An Oak 35" dia., bears S.35°W., 145 lks. dist., with scribe marks WC ¼ S7 CS visible on partially healed double blaze.

Fd. OK, Feb. 1983 by H. Northcraft - M 93-56

Fd. OK - Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Oct. 1997 - C.S. File 64/79-9