

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6606)

Set post cor. secs. 5, 6, 7 and 8, from which
A Fir 10" dia., bears N.82°W., 5 lks. dist.
A Fir 9" dia., bears S.33°W., 23 lks. dist.
A Fir 12" dia., bears S.34°E., 36 lks. dist.
A Chinquapin 12" dia., bears N.34°E., 74 lks. dist.

H.L. Eppstein - W.S. Crear; W.G. Reetz; R.T. Dunton - (Date?)
C.S. File 4/70

Set 1" x 1" x 30" Iron bar from old BT, SE.
Marked new BTs:
A R.Fir 30" dia. S.66°30'E., 34.0 ft.
A R.Fir 20" dia. S.15°00'W., 5.9 ft.
A R.Fir 24" dia. N.76°00'E., 131.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Sept. 1958 - C.S. File 49/100-15

Found - 1" x 1" Iron bar at corner as recorded by Eppstein.
24" now 36" Fir, N.76°E., 169.3 ft. (Rec. 131.0 ft.), shows bark scribing "BT"
30" now 40" down Fir, S.66½°E., 34.0 ft., shows bark scribing "BT" "S8".
No trace of orig. SE. BT nor Eppstein's SW. BT.
I do not set brass cap at corner. Iron rod lies 2.0 ft. S. of fence corner, fences running N. and W.
New BTs- 8" R.Fir bears S.56½°W., 36.6 ft. scribed S7 T29S R8W CS BT.
11" Cedar bears S.10°E., 53.9 ft. scribed S8 T29S R8W CS BT.
6" R.Fir bears N.82°E., 21.7 ft. scribed S5 T29S R8W CS BT.
No suitable trees near to NW.

Fd. OK, June 1980 by R. Hendrick - M 84-19

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 17009)

The Sec. cor., perpetuated and recorded by Eppstein in 1926, and further perpetuated and recorded by Byron in 1958, and accepted as a careful and faithful perpetuation of the
(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

position of the original cor., monumented with an iron bar, 1" x 1" firmly set, projecting 3" above ground, from which a bearing tree mkd. by Eppstein

A Fir snag 36" dia., bears N.76°E., 256½ lks. dist., with fragmentary scribe marks visible on bark blaze.
and bearing trees mkd. by Byron

A Fir 10" dia., bears N.82°E., 33 lks., with healed blaze.

A Fir 12" dia., bears S.56½°W., 55½ lks. with healed blaze

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T	29	S	R	8	W
	S	6	S	5	
	S	7	S	8	
				1980	

from which new bearing trees

A Fir 10" dia., bears S.31°E., 46 lks. mkd. T29S R8W S8 BT

A Fir 4" dia., bears N.39°W., 12½ lks., mkd. X BT.

Deposit the iron bar alongside the iron post.

Fd. OK, Aug. 1995 by Mark Smalley - M 119-69

Fd. OK Feb. 2000 by G. Lang - M134-30

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2159, surveyed April/May 2007 - (DCSO rec Vol. 55 Pg 21505) & 2008 BLM plat

The cor. of secs. 5, 6, 7, & 8, monumented with on iron post, 2½" dia., firmly set, projecting 5" above the ground, with brass cap mkd. as reported in 1980-82, from which the remains of a BT mkd by Eppstein, in 1926, reported by Jelley & Rogers

A fir snag, 36" dia., bears N.76°E., 169.3 ft., with fragmentary scribe marks visible in the bark.

and the remains of bearing trees mkd. by Byron. in 1958. reported by Jelley and Rogers

A fir, 19" dia., bears S.31°E., 30.4 ft with healed blaze.

A fir, 6" dia., bears N.39°W., 8.2 ft. with healed blaze.
and a new BT

A fir, 11" dia., bears S.66¼°W., 12.4 ft., mkd: T29S R8W S7 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.