

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 240140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1972, surveyed April/May 2001- (DCSO rec. Vol. 54 Page(s) 20962-3)

Point for the center ¼ sec. cor. of sec. 32, at intersection with the E & W centerline.
Drive a rebar, 36" long, 5/8" dia., 30" in the ground into a tree root, with aluminum cap, 2½" dia., mkd.

T29S R8W
C ¼
S 32
2001

from which

- A fir, 18" dia., bears N.62½°E., 3.4 ft., mkd. C¼ S32 BT.
- A fir, 16" dia., bears S.7¼°W., 4.1 ft., mkd. C¼ S32 BT.
- A stainless steel post, 28" long, 2½" dia., set 20" in the ground for a reference monument, bears N.42°25'59"W., 9.90 ft. with brass cap mkd. RM T29S R8W C¼ S32 9.90 FT TO COR 2001 and an arrow pointing to the corner.

Fd. BC & 2 BTs. by Gary Smither, 7/2007 - M153-78