

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6603)

Set ¼ sec. post, from which
An Oak 30" dia., bears N.86°E., 1216 lks. dist.
An Oak 18" dia., bears S.87°E., 1257 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - Wit: W.S. Crear; C. McCann; Wm. M. Porter - Dec. 1927 - M 1-63; Vol. 3 Pg. 281; C.S. File 7/38

Set sandstone 3" x 10" x 16", chiseled ¼ and X from original BT. Old blaze badly scarred up.
New BTs- A 14" Fir S.85¼°E., 338 lks. scribed ¼ S20 CS BT.
A 14" Fir N.60°E., 392 lks. scribed ¼ S17 CS BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Sept/Oct. 1958 - C.S. File 49/100

Found Rock at corner with X on top and both BTs as recorded by Irving. BTs show good scars. I do not open, now 30" dia. Set brass cap at corner and alongside corner stone mkd cap: "¼ S17 S20 County Surveyors Office 1958 T29S R8W".
I do not scribe new BTs.

Fd. OK, Dec. 1984 by E. Bloom - M 98-13
Fd. OK, Sept. 1986 by OSHD - C.S. File 63/9-23
Fd. OK, Nov. 1997 by C. Sweeden - M 127-73

BLM dependent resurvey by Bryan s. Seibold, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1776, surveyed Oct./Nov. 1995 - (DCSO records Vol. 52 Page(s) 19926)

The ¼ sec. cor. of secs. 17 & 20, perpetuated by Irving, Deputy County Surveyor, in 1927, from original evidence no longer in existence, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, further perpetuated by Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, monumented with an iron post, 1¼" diam., firmly set, projecting 3" above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T29S R8W

¼ $\frac{S\ 17}{S\ 20}$
1958

continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees mkd. by Irving
A fir, 46" diam., bears N.59½°E., 392 lks., with healed blaze.
A fir, 46" diam., bears S.87°E., 340 lks., with healed blaze.
The corner is located in a Christmas tree plantation and on the S. side of a 7 in. diam. wood post, and W., 3.65 chs. dist. of Kirkendahl Road (County Road No. 128A), asphalt-surfaced, 30 lks. wide, extends N. and S.

Fd. IP w/BC - James M. Standley - For: ODOT - 12/2007 - St. Hwy 42-013B

Fd ok by K. DeGroot, 7/2014 - M168-33