

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 240440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1776, surveyed Oct./Nov. 1995 - (DCS0 records Vol. 52 Page(s) 19926-7)

Point for the center ¼ sec. cor. of sec. 17, at intersection with the E. & W. center line.
Set a stainless steel post, 28" long, 2½" diam., 40" in the ground, with brass cap mkd.

T29S R8W
C ¼ S 17
1995

from which

A stainless steel post, 28" long, 2½" diam., set 22" in the ground, for a reference monument, with silver "DEEP-1" magnetic marker at base, bears N.35°E., 14 lks., with brass cap mkd. RM C1/4 S17 9.2 FT TO COR 1995 and an arrow pointing to the corner.

A metal flag pole, 3" diam., set in concrete, bears N.74¼°E., 116 lks.

The SW. cor. of a pump house foundation, 3½ ft. x 4 ft., bears S.45 ¾°E., 185 lks., long side extends N.

The corner is located S.86°W., 0.095 chs. of a fence corner, with woven wire fence extending N.10°W. and E., and W., 3.75 chs. dist. of Kirkendahl Road (County Road No. 128A), asphalt-surfaced, 30 lks. wide, extends N. and S.

Fd ok by K. DeGroot, 7/2014 - M168-33

Fd BC by B Heichel, 7/2021 - M179-52

Fd BC by N Hibbs, 12/2023 - M178-76