

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6606)

Set ¼ sec. post, from which
A Chinquapin 8" dia., bears N.49°E., 30 lks. dist.
A Chinquapin 6" dia., bears S.64°E., 23 lks. dist.

Survey by Russell D. Hendrick - For: Marion Mooney - June 27, 1980 - M 84-19

Set 1/4 Cor. by proportionate with a 5/8" Iron rod.
New BTs- 5" W.Fir N.46°37'W., 20.1 ft. scribed ¼ S5 BT.
9" W.Fir S.19°25'E., 21.1 ft. scribed ¼ S8 BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 17008)

The ¼ sec.cor., reestablished by Hendricks in 1980, and accepted as a careful and faithful restoration of the position of the cor., monumented with an iron rod, 1/2" dia., firmly set, projecting 2" above ground, from which bearing trees mkd. by Hendricks
A W.Fir 5" dia., bears N.46½°W., 31½ lks. dist., with scribe marks ¼ S5 BT visible on open blaze.
A Hemlock 10" dia., bears S.17½°E., 33 lks. dist. with scribe marks ¼ S8 BT visible on open blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 29 S R 8 W
1/4 $\frac{S 5}{S 8}$
1980

Deposit the iron rod alongside the iron post.

Survey by Mark Smalley - For: Roseburg Resources and Ninette West - Aug. 1995 - M 119-69

Found - 1980 Cadastral brass cap/iron pipe.
10" Hemlock S.17½°E., 21.8 ft., snag scribe visible.
New BTs- 8" Chinquapin S.2°E., 36.8 ft. "¼ S BT"
6" Fir S.22°W., 32.9 ft. "¼ S BT"
6" Fir S.60°W., 32.3 ft. "¼ S BT"

continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2159, surveyed April/May 2007 - (DCSO rec Vol. 55 Pg 21505) & 2008 BLM plat

The ¼ sec. cor. of secs. 5 & 8, monumented with on iron post, 2½" dia., firmly set. projecting 4" above the ground, with brass cap mkd. as reported in 1980-82, from which the remains of a BT by Hendricks, in 1980, reported by Jelley & Rogers

A decayed hemlock stump size indeterminate, bears S.17½°E. 21.8 ft. with no marks visible.

and bearing trees mkd. by Smalley, in 1995

A fir, 9" dia., bears S.23½°W., 33.3 ft. with healed blaze

A fir, 10" dia. bears S.60¾°W., 32.4 ft. with healed blaze and a new bearing tree

A fir, 6" dia., bears N.7¼°W., 6.1 ft., mkd: ¼ S5 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

NAD 1983 (CORS 96)

Latitude 43°04'09.24"N

Longitude 123°40'53.59"W