

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & S 32, T28-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCS0 recs Vol. 14 Pgs 5794-95)

Set ¼ sec. post, from which
A Fir 40" dia., bears S.40°W., 4 lks. dist.
A Fir 5" dia., bears N.35°E., 19 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; crew - Sept. 6, 1957 - C.S. File 49/12-9

Found - 40" now 50" Fir S.40°W., 26 ft*., shows old scribing "¼ S BT", bark scribed. Also newer scribing "¼ S BT".
I open 5" now 14" W.Fir N.35°E., 12.5 ft. Good scribe marks "BT".

BTs check record bearings and distances.

Set Brass cap at cor. mkd: County Surveyors Office

¼ $\frac{S \ 32}{S \ 5}$ T28S R8W
T29S

1957

I rescribe 14" W.Fir which bears N.35°E., 12.5 ft ¼ S32 CS BT * on 1957 hand written report the dist. appears to be 26 ft. but per GL0 orig. survey the dist is 4 lks. or 2.6 ft. (DCS0 LEM & JC 10/21/1999)

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 9/21/1999 - C.S. File 66/12-30

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 18" above ground. 1957
40" now 60" dia., D.Fir with bark scribing "¼S" and other illegible bark scribing visible bears S.40°W., 4.3 ft. to center of base (rec. S.40°W., 12.6 ft. agrees well with orig. bark scribed face) OBT.
5" now 22" dia., 1½ ft. high rotted Fir stump illegible scribing visible, bears N.35°E., 12.5 ft. (agrees with rec.) OBT

New BTs- 7" dia., G.Fir double blazed & scribed "¼ S32 CS BT" bears N.84°E., 9.7 ft.

15" dia., G.Fir double blazed & scribed "¼ S5 CS BT" bears S.63½°E., 26.4 ft.

10" dia., Chinquapin double blazed & scribed "¼ S32 CS BT" bears N.18°W., 62.1 ft.

Fd OK by DCS0, SJF & JL 1/2019 - C.S. File 67/46-1

Lat: 43°05'02.091087882" Long: 122°57' 44.268210310"