

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6595)

-----  
Marked a Fir 8" dia. for ¼ sec. cor., from which  
A Fir 12" dia., bears S.35°W., 22 lks. dist.  
A Fir 6" dia., bears N.45°E., 20 lks. dist.

A. Boyer, Surveyor - Wit: Shellabarger; Jim Ruckert; B. Denn; John - 1939 - C.S. File 16/25

-----  
2 x 2 Oak post, from which  
40" Cedar, N.55½°E., 23.0 ft.  
36" Fir, S.48°W., 14.8 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Oct. 1958 - C.S. File 49/100-44

-----  
Found - Boyer BT, a 40" Cedar N.55½°E., 23.0 ft., good condition, scribing visible.  
Boyer BT, 36" now down Fir, S.48°W., 14.8 ft., shows good bark scribing.  
Find scribed stake at corner.  
I do not find either original BT.

Set Brass cap alongside stake & mkd: County Surveyors Office  
T 29 S R 8 W  
¼ S32 | S33  
1958

New BT - 7" W.Fir bears S.79°W., 17.2 ft. scribed ¼ S32 CSBT.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1972, surveyed April/May 2001- (DCSO rec. Vol. 54 Page(s) 20956-7)

-----  
The ¼ sec. cor. of secs. 32 & 33, reestablished at proportionate dist by Boyer in 1939, subsequently perpetuated by Byron, in 1958. There is no remaining evidence of the original corner, therefore this point is accepted as the cor.; monumented with an iron post, 1½" dia., firmly set, projecting 13" above ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Boyer

A cedar, 45" dia., bears N.57½°E., 25.1 ft., with scribe marks S33 T29 R8 CS BT visible on a partially healed blaze.

A roothole bears S.30¾°W., 14.8 ft., with fallen sawed stump, 32" dia., lying alongside, with no marks visible and a bearing tree mkd. by Byron

continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir, 21" dia., bears S.79°W., 17.2 ft., with a healed double blaze.