

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6595)

Set post cor. secs. 28, 29, 32 and 33, from which
A Fir 30" dia., bears N.57°W., 51 lks. dist.
A Fir 6" dia., bears S.22°E., 23 lks. dist.
A Cedar 7" dia., bears S.23°W., 6 lks. dist.
A Laurel 12" dia., bears N.38°E., 45 lks. dist.

H.L. Eppstein, County Surveyor - Wit: B.A. Lane; Giles; Ben Bennet - June 2, 1931 - C.S. File 18/23

Set from old original BTs. Set a 4" x 4" x 36" Fir stake, 18" in ground, from which
Fir 60" dia. N.57°W., 51 ft. O.B.T.
Laurel 12" dia. N. E., laying down. O.B.T.
Fir 12" dia. S.43°W., 35½ ft.
Cedar 30" dia. S.5°E., 33 ft.
Fir 8" dia. N.35°30'E., 22.8 ft.

(Note: the above corner description was also given in renewal #84 in former corner renewals as by Cole in 1923, C.S. File 16/25 - but notes given to me from C.S. 16/25 was given as "Boyer" in 1939 which also describes same BTs. (V.Laugen, April 1997)

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Jan. 4, 1961 - C.S. File 51/163-4

Found 30" Cedar S.5°E., 33 ft., down, scribing visible, and a 4x4 Cedar post with scribing.
Set 1" x 30" Iron pipe, from which
6" Cedar S.25¼°E., 138.5 ft.
6" W.Fir N.70½°W., 118.2 ft.
5" W.Fir S.80°W., 52.0 ft.
8" R.Cedar N.46°E., 126.6 ft.

Survey by Ronald Geisler - For: Champion International - Oct. 15, 1986 - C.S. File 63/34-49

Found - 1½" I.P. (Rec. 1" I.P.) extends 5" above ground.
6" Cedar, now rotting 5 ft. tall snag, bears S.25¼°E., 138.5 ft., scribe visible. (1961)
6" Fir, now down and rotted, bears N.70½°W., 118.2 ft., scribing partially visible. (1961)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

12" W.Fir bears S.80°W., 51.77 ft., (Rec. 52.0 ft.)
Healed face. (1961)
14" Cedar, bears N.46°E., 126.6 ft. scribe visible.
(1961)
New BTs- 12" D.Fir bears S.47°E., 28.5 ft. scribed T29S R8W
S33 BT.
6" D.Fir bears N.67°W., 23.47 ft. scribed T29S R8W
S29 BT.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under
Group #1972, surveyed April/May 2001- (DCSO rec. Vol. 54
Page(s) 20957-8)

The cor. of secs 28, 29, 32, & 33, perpetuated by Eppstein,
in 1931, from original evidence no longer in existence,
further perpetuated by Johnstone, in 1961, and further
perpetuated by Geisler, in 1986; monumented with an iron
pipe, 1¼" dia., firmly set, projecting 6" above ground, with
no cap, from which the remains of bearing trees mkd. by
Johnstone
A cedar, 17" dia., bears N.46°E., 126.6 ft., with scribe
marks 29 R8W S28 on upper and BT visible on lower
partially healed blazes.
A cedar stob, 6" dia., bears S.25¼°E., 138.5 ft. , with
scribe marks 33 on upper and BT visible on lower
unhealed blazes.
A fir, 15" dia., bears S.80°W., 51.8 ft., with a healed
blaze.
and bearing trees mkd. by Geisler
A fir, 21" dia., bears S.47°E., 28.5 ft., with a healed
double blaze.
A fir, 14" dia., bears N.67°W., 23.5 ft., with a healed
double blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the
ground, directly over the existing iron pipe, with brass cap
(properly) mkd.
T29S R8W
S 29 | S 28
S 32 | S 33
2001
Deposit a magnet in a white plastic case at the base of the
stainless steel post.
Corner is located 54 ft. S & 73 ft. W of Road No. 29-8-29.3,
a gravel road 12 ft. wide, bears S.51°E. & N.51°W.

FD. & used on BLM retracement by A. Bert Skeesick, Cad.
Surveyor, under Group #2300, Nov. 2006 - (DCSO records Vol.
55 Page 21464 {Info on plat, copy filed in Vol 55}) CONT.

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2196, Surveyed Feb/March 2008 - (DCSO records Vol. 56 Page(s) 22286-7)

The cor. of secs. 28, 29, 32, and 33, monumented with a stainless steel post, firmly set, projecting 4" above the ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by Johnstone, reported by Skeesick

A cedar, 18" dia., bears N.46°E., 126.6 ft., with fragmentary scribe marks visible on a partially healed double blaze.

A cedar stob, 6" dia., bears S.25¼°E., 138.5 ft., with scribe marks 33 visible on upper and B visible on lower decayed, partially healed blazes.

A fir, 17" dia., bears S.80°W., 51.8 ft., with a healed blaze.

and BTs mkd. by Geisler, reported by Skeesick

A fir, 24" dia., bears S.47°E., 28.5 ft., with a healed blaze.

A fir, 16" dia., bears N.67°W., 23.5 ft., with a healed blaze.