

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6597)

-----  
Set ¼ sec. post, from which  
A Fir 15" dia., bears S.20°E., 16 lks. dist.  
A B.Oak 10" dia., bears S.46°W., 37 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - Wit: W.S. Crear; C. McCann; Wm. M. Porter - Dec. 1927 - Vol. 3 Pg.281; C.S. File 7/38; M 1-63

-----  
Set Ford axle with gear attached for corner from one original BT, which I remarked in the bark.  
A 30" Fir S.20°E., 16 lks.  
A 28" Fir N.60°W., 60 lks. mkd. ¼ S20 CS BT., new BT.  
(May 15, 1936 - this tree has been cut down and grubbed out)  
New BT - An 18" Fir N.13°E., 91.0 ft. mkd. ¼ S21 CS BT., bark blaze. A. Boyer - Wit: Ralph Richter.

Douglas Co. Surveyor - James Byron, Deputy - Jan. 22, 1954 - C.S. File 45/235

-----  
Found geared axle and old BT, 30" Fir S.20°E., 16 lks. in good condition.  
Blazed and scribed new trees:  
6" R.Fir N.23°W., 123.6 ft. mkd. ¼ S20 CS BT.  
8" R.Fir N.79°E., 219.9 ft. mkd. ¼ S21 CS BT.

James Byron, Deputy Co. Surveyor - For: Douglas Co. Health Dept. - April 1962 - C.S. File 52/114 - RM 2-20

-----  
Found - Now 34" Fir stump S.20°E., 10.6 ft. No scribing found, bark gone, may have been bark scribed.  
Now 12" Fir N.79°E., 219.9 ft. Shows good scars.  
NW. Bt, 1954 renewal, not found.  
We do not find geared axle set for corner. BLM men state geared axle was in place and at fence corner in Sept. 1961.  
Brass cap at corner mkd. County Surveyors Office 1962 1/4 S20 S21 T29S R8W.  
New BT - 17" Cedar bears N.18°W., 207.2 ft. scribed ¼ S20 CS BT.

Fd. OK, Dec. 1984 by E. Bloom - M 98-13

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas co. Surveyors Office - L.E. Monrean, Deputy - R.W. Smith; S.J. Flause, crew - May 2, 1985 - C.S. File 62/28-2

Found - 1962 1" I.P. with brass cap set firmly 10" high. Is along top of 3 1/3 ft. high cut bank.

(Distances to found trees are record per 1962. Residential area, considerable brushing necessary.)

Orig. 15" Fir now a 34" stump, bears S.20°E., 10.6 ft. No scribing.

An 8" now 25" Fir with well healed single blaze, bears N.79°E., 219.9 ft.

A 17" now 30" Cedar with well healed blaze, bears N.18°W., 207.2 ft.

Survey numbers M 98-13 and M 98-14, report no bearing trees.

New Accessories:

Chiseled X in top and at East end of 12" dia., concrete culvert running easterly-westerly on S. side of road "Our Lane", bears S.88½°E., 27.0 ft.

A utility pole 9" dia. and marked "1 248 10", bears N.31½°E., 37.9 ft.

Fd. OK, Jan. 1995 by K. DeGroot - M 121-33 & C.S. File 63/52

Fd. Ok Nov. 2007 by R. Brown, 2008-0012

Fd. BC June 2013 by D. Edwards, M165-65

Fd. BC 4/2018 by R. Ward, M174-51

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 6/10-2019 (filed 1/28/2021) - C.S. File 67/48-22

Found - A 1" I.D. iron pipe by Byron, in 1962, firmly set, projecting 13" above the ground in a with a 2½" dia. brass cap 9properly) mkd

Orig. BT by D Hawthorn, USGLO Deputy Surveyor, in 1855:

A 4" Mag Hub set in the center of a 34" dia. x 1.5' tall D.Fir stump bears S.20°E., 12.0 ft (Rec 16 lks)

A BT by Byron, Deputy Co. Surveyor, in 1962:

A 42" dia. x 3' tall cedar stump bears N.18°W., 207.2 ft with a healed blaze.

A BO by Monrean, Deputy Co. Surveyor, in 1985:

A 9" dia. utility pole marked "I 248 10" bears N.3½°E., 37.9 ft.

New BT - A 16" dia. D.Fir bears S.88½°E., 53.7 ft scribed "¼ S21" & "CS BT" on a double blaze.

A 7" dia. Madrone bears S.64°W., 10.3 ft scribed "X" & "BT" on a double blaze.

Note - Compass declination 14¾°E.

The corner falls in the cut bank on the South edge of Our Lane Road. Continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

All BTs have BT Tags attached. All new BTs have double blazed faces with bearing measured to the center of the tree at the root crown and distances measured to a 4" Mag Hub in the side and center of the root crown.

Geodetic coordinates

Latitude: 43°00'57.25" N.

Longitude: 123°23'39.27" W.

DATUM: NAD 83

SOURCE: GeoXT6000