

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6599)

Set post cor. of secs. 4, 5, 8 and 9, from which

- A Fir 36" dia., bears N.53°W., 91 lks. dist.
- A Fir 18" dia., bears N.53°E., 160 lks. dist.
- A Laurel 4" dia., bears S.85°W., 61 lks. dist.
- A Laurel 4" dia., bears S.66°E., 41 lks. dist.

Survey by Russell D. Hendricks - For: Marion Mooney - June 27, 1980 - M 84-19

Section corner set by double proportion. Found brass cap set by concurrent BLM survey to be exactly located. Cap marked BLM 1980 S4 S8 S9 S5 T29S R8W., from which

- 11" D.Fir S.12°53'W., 11.7 ft. scribed T29S R8W S8 BT.
- 6" D.Fir N.84°46'W., 3.2 ft. scribed T29S R8W S5 BT.
- 11" D.Fir N.30°31'E., 15.6 ft. scribed T29S R8W S4 BT.
- 8" D.Fir S.54°00'E., 27.0 ft. scribed T29S R8W S9 BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 17004-005)

Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd:

T	29	S	R	8	W	
		<u>S</u>	<u>5</u>		<u>S</u>	<u>4</u>
		S	8		S	9
						1980

from which

- A Fir 9" dia., bears N.29 3/4°E., 24 lks. dist. mkd. T29S R8W S4 BT.
- A Fir 8" dia., bears S.54½°E., 41½ lks. dist. mkd. T29S R8W S9 BT.
- A Fir 11" dia., bears S.12¼°W., 18 lks. dist. mkd. T29S R8W S8 BT.
- A Fir 6" dia., bears N.85 3/4°W., 6 lks. dist. mkd. T29S R8W S5 BT.

FD. BC & 4 BTs, Set 6' steel post 2' north, by D. Edwards, 7/2011 - C.S. File 65/74-8