

PRIMARY CORNER DESCRIPTION West 1/16 cor. bet. secs. 9 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ben B. Irving, Deputy Co. Surveyor - For: Louis Papst - Oct. 25, 1938 - C.S. File 37/200

Set 4" x 4" x 36" Cedar post mkd. C.S W. side; S9 on N. side; S16 on S. side and W 1/16 on E. side., from which
10" Fir S.84°W., 16.9 ft.
10" Fir N.55°W., 28.2 ft.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 17001-02)

Point for the W 1/16 sec. cor. of secs. 9 and 16.
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd. W 1/16 $\frac{S\ 9}{S\ 16}$
1980

from which
A Fir 4" dia., bears N.83¼°W., 9½ lks. dist. mkd. X BT.
A Fir 7" dia., bears S.88½°E., 20 lks. dist. mkd. W 1/16 S16 BT.
From this point, a car axle 1" dia., firmly set, projecting 10" above ground, not of known record, bears N.8°E., 22½ lks. dist.

Corner report by OSHD, Sept. 16, 1986 - C.S. File 63/9 and by John Read, Oct. 1988, C.S. File 64/6-12

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - March 28, 1990 - C.S. File 64/6-12

Position of corner was referenced by John Read, OSHD. A hub and tack is found at OSHD position of referenced corner, this hub and tack checks well with R.P. hub and tacks set by Read. Position of BLM BC/IP falls under fill of new highway construction. 1" car axle noted in 1980 BLM resurvey and W 1/16 cor. and BTs per Irving are not found. No accessories found. Apparently BTs cut down and covered up in construction.
Set a 2 3/8" dia. DCSO brass cap on a 1 3/8" O.D. x 31" long I.P., is set West 111.0 ft. from referenced corner. DCSO BC/IP protrudes 9" above ground. Cap stamped: "Douglas County Surveyors Office T29S R8W W 1/16 S9 S16 BO 1 East 111 ft. to cor. 1990".
From referenced position of DCSO BC/IP (BO1):
New BTs- 12" W.Fir double blazed and scribed "BO 1 W 1/16 S9 CS BT" bears N.19°E., 4.6 ft.

(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 320500

PRIMARY CORNER DESCRIPTION West 1/16 cor. bet. Secs. 9 & 16

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

6" W.Fir double blazed and scribed "BO 1 W 1/16 S16
CS BT" bears S.86°W., 11.1 ft.