

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6596)

-----  
Set ¼ sec. post, from which  
A Fir 24" dia., bears N.30°W., 43 lks. dist.  
A Hemlock 10" dia., bears S.40°W., 23 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - W Penley, crew - March 17, 1971 - C.S. File 54/38-31

-----  
Found - Orig. 24" now 48" Fir, N.30°W., 28.4 ft., no original scribing found. We do find good bark scribing on NE. face, "¼ S21 T29S R8W BT 1580"  
No trace of original SW. bearing tree.  
Do find scribed stake at corner and Cedar that shows good scribing bears S.31°W., 24.0 ft.

Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R 8 W  
¼  $\frac{S\ 21}{S\ 28}$   
1971

No new bearing trees scribed.  
Corner at bottom of small draw.

Statement by Boyer filed in C.S. File 54/38:  
I, Arthur Boyer, state that I renewed the ¼ corner to sections 21 and 28, T29S R8W WM in 1958 by bark scribing the original NW. Fir BT on which I observed bark scribe marks and that, at that time, I set a scribed stake at the ¼ corner using record bearing and distance from the Fir BT. Also, that I scribed a small Cedar in SW. quad for BT in sec. 28.

Fd. OK, Jan. 1995 by K. DeGroot - M 121-33; C.S. File 63/52

Kris DeGroot - Lester Fanning & Joel Herzberg - 1/21/2009 - C.S. File 65/66-3

-----  
Found - 1¼" galv. iron post, firmly set, projecting 10" above the ground with a 2½" diameter brass cap (properly) stamped. From which an original bearing tree by Hathorn in 1855:  
A 64" Fir bears N.30°W., 28.4 ft.  
And a bearing tree by Boyer in 1958 per CS 54/38:  
A 27" Cedar bears S.3 low., 24.0 ft. with healed face.  
New BTs- A 12" Hemlock bears N.2°W., 24.3 ft. which I scribe "1/4 S21 BT" on a double face. cont. next pg

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 11" Hemlock bears S.51°E., 10.5 ft. which I scribe  
"¼ S28 BT" on double face.  
All new bearing trees have double blazed faces with a brass  
washer stamped "PLS 1941" nailed into the lower blaze.  
Bearings are taken to the center of the tree at the root  
crown and distances are measured to an aluminum nail in the  
root crown at the side and center of the tree. All bearing  
trees have a 6" red band painted around the tree and the  
blazed face painted red and Bearing Tree tag