TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6597)

Set ¼ sec. post, from which
Chinquapin 10" dia., bears S.38°W., 141 lks. dist.
Chinquapin 9" dia., bears N.7°E., 47 lks. dist.

Survey by Kristian DeGroot, LS #1941 - For: Joel & Ora Kuhse; Lone Rock Timber and Silver Butte Timber Co. - Jan. 1995 - M 121-33 and C.S. File 63/52

No original corner evidence remains.
Proportionate measurement.
Set 1" x 30" galv. I.P., 28" in the ground, with 2½" brass cap stamped:

T29S R8W
¼ S 16
S 21
1994
PLS 1941

from which
7" D.Fir bears N.26°W., 30.9 ft. scribed ¼ S16 BT.
13" D.Fir bears S.71°W., 20.1 ft. scribed ¼ S21 BT.
5/8" x 30" iron rod w/plastic cap "BTS ENG-SURV" bears S.26°E., 19.6 ft.
5/8" x 30" Iron rod w/plastic cap "BTS ENG-SURV" bears N.71°E., 25.1 ft.
and a monument not of record:
1" Iron pipe bears S.10°50'52"E., 1.51 ft.

Fd. Ok Feb. 2007 by Ken Hoffine - M152-41
Fd. Ok by R Quimby - 10/2017 - C.S. File 65/99-11