

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6598)

Set ¼ sec. post, from which
An Oak 10" dia., bears N.3°W., 142 lks. dist.
A Laurel 10" dia., bears S.20°W., 88 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - Wit: R.L. Irving; Louis Papst - Oct. 28, 1938 - C.S. File 37/200; C.S. File 15/11

Location identified by both orig. BTs, badly rotted.
Set ¾" x 16" Iron bar with 4" x 4" post alongside.
A Fir 22" dia., bears N.48°E., 22.7 ft. blazed and scribed ¼ S9 CS BT.
A Fir 18" dia., bears S.76¼°W., 21.5 ft. blazed and scribed ¼ S16 CS BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Oct. 31, 1958 - C.S. File 49/100-46

Found - ¾" x 16" car brake lever arm at corner and both BTs as recorded by Irving.
18" now 24" Fir stump S.76¼°W., 21.5 ft., I open and find good scribing "BT".
22" now 26" Fir shows good scars, N.48°E., 22.7 ft. I do not open.
Also find "+ B0" on 10" x 10" x 4 ft. stone, bears N.25°E., 13.3 ft.
Set Brass cap at cor. and alongside lever mkd:
County Surveyors Office
T 29 S R 8 W
¼ $\frac{S \ 9}{S \ 16}$
1958
New BT - 28" R.Fir bears S.34½°E., 21.6 ft. scribed ¼ S16 CS BT.

Douglas Co. Surveyors Office - R.B. Kimberling; P.L. Earle, crew - March 1, 1978 - C.S. 59/46-62

Found - A 1" I.P. with 1958 DCSO brass cap set 13" above ground.
22" now 30" D.Fir bears N.48°E., 22.7 ft. with a well healed double blaze.
18" Fir stump bears S.76¼°W., 21.5 ft. with cut out section of blaze on top of stump showing reverse scribing "BT".
(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 28" now 32" D.Fir bears S.34½°E., 21.6 ft. with a well healed double blaze.
No new monument set.
New BT - 10" D.Fir bears N.31°W., 77.4 ft. double blazed and marked ¼ S9 CS BT.
Corner is approx. 300 ft. East of Hwy. #42.

Fd. July 1986 by OSHD - C.S. File 63/9-14

Fd. and Used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 17001)

Found OK by M. Farr, Nov. 1998 - LP 1998-0139
FD. Ok by Ken Hoffine - Sept. 2006 - M151-47

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 10/30/2006 - C.S. File 67/14-36

Found - 2½" BC, properly mkd, protrudes 12" above ground.
28" now 30" dia., x 4 ft. tall D.fir stump, fully healed double blaze, with angle cut top, bears S.34½°E., 21.6 ft. (agrees w/rec) 1958
30" now 28" dia., x 2½ft. rotted D.Fir stump fully healed lower blaze bears N.48°E., 23.3 ft. (rec. N.48°E., 22.7 ft.)
18" now 18" dia., x 1½" ft. tall very rotted D.Fir stump, no marks visible bears S.76¼°W., 21.5 ft. (agrees w/rec.) 1938
10" now 26" dia., x 1½ ft. tall rotted stump evid. of low blaze bears N.31°W., 77.4 ft. (agrees w/rec.) 1978
10x10x4 ft. tall stone with chiseled "+B0" bears N.26°E. 13.3 ft to "+" (Rec N.25°E. 13.3 ft) 1958

New - 16" dia., I.Cedar double blazed & scribed "¼ S9 CS BT" bears N.25¾°W., 77.8 ft.
7" dia., D.Fir double blazed & scribed "¼ S16 CS BT" bears S.81°W., 25.2 ft.
12" dia., D.Fir double blazed & scribed "¼ S16 CS BT" bears S.30°E., 15.5 ft.

New - Corner lies on moderate SSW facing slope. Approx. 15 ft. Southerly of brushed power line R/W and approx. 150 ft. easterly of Quiet Mtn. Rd.
Compass decl. 16½°E.

continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - 9/2014 - M166-24A-D & M166-40 A-D

Found - 2½" brass cap stamped Co Surveyors Office dated 1958
30" Fir stump 6' tall with healed face and tag dated 10/58; S.35°E., 21.6'.
15" Fir with visible scribe and tag dated 10/30/06; S.30°E., 15.5'.
10" Fir with visible scribe and tag dated 10/30/06 S.81°W., 25.2'.