

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 378100

PRIMARY CORNER DESCRIPTION C.C. for secs. 3 & 4 only, T30-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 16 Page(s) 6611)

-----  
Set a Fir post, triangular, 4 ft. long, 4" dia., 20" in the ground and mkd. T29S R8W S33 on N.; T30S R8W S3 on the SE.; and S4 on SW. Also 3 notches each on the E. and W. angles of same and from which

A Fir 12" dia., bears S.52°E., 16 lks. mkd. T30S R8W S3 BT

A Fir 15" dia., bears S.74°W., 13 lks. dist. mkd. T30S R8W S4 BT.

A Laurel 14" dia., bears N.35°W., 23 lks. dist. mkd. T29S R8W S33 BT.

-----  
A. Boyer, Surveyor - Wit: Gee and Hendrickson - April 1949 - C.S. File 40/192

-----  
Found orig. BT, S.52°E., 10.6 ft. with scribe in bark.

Set 3" Yew post for corner, from which new BT

12" Fir S.13°30'W., 23.7 ft. mkd. BT S4 T29 R8W 1581

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - April 1967 - C.S. File 54/38-16

-----  
Found - Original post "34".

Orig. 12" now 14" D.Fir S.52°E., 10.5 ft., shows bark scribing "T R8"

12" now 14" W.Fir S.13½°W., 23.7 ft., shows scribing "BT S4 T30S R8W 1581".

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 8 W

S 33

S 4 | S 3

1967

Rescribed orig. BT:

14" D.Fir S.52°E., 10.5 ft. scribed "T30S R8W S3 CSBT"

New BT - 8" W.Fir N.8½°E., 13.8 ft. mkd. T29S R8W S33 CSBT.

-----  
Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Jan. 9, 1980 - M 79-15

-----  
Found - 1967 DCSO brass cap and iron pipe.

Set 5/8" x 36" iron rod and alum. cap South 5.30 ft. on true Tp. line, from which

16" Fir S.79°E., 8.6 ft.

14" Fir S.18°W., 18.5 ft.

12" Fir N.7°E., 19.1 ft.

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 378100

PRIMARY CORNER DESCRIPTION C.C. for Secs. 3 & 4 only, T30-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1240, surveyed Feb./July 1985 - (DCSO records Vol. 47 Page(s) 18112)

-----  
The Sec. Cor., perpetuated & recorded by Boyer in 1949, & further perpetuated & recorded by Powell in 1967, monumented with an iron post 1¼" dia., firmly set, projecting 14" above ground, with brass cap mkd. in 1967, from which the remaining original bearing tree

A Fir 15" dia., bears S.52°E., 16 lks., with healed blaze. and a bearing tree mkd. by Boyer

A Fir 17" dia., bears S.13°W., 37 lks., with fragmentary scribe marks visible on partially healed blaze. and a bearing tree mkd. by Powell

A Fir 13" dia. bears N.7 3/4°E., 20 lks. with fragmentary scribe marks visible on partially healed blaze.

From this point, a point established & recorded by Johnstone in 1979, bears S.0°15'E., 0.08 chs., monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, with alum. cap 2" dia., mkd. 1979 T29S 33 R8W 4 3 T30S LS 498.

Gary Smithers - March 16, 2001 - C.S. File 65/37-1

-----  
Found - 1967 County brass cap on iron pipe firmly set.  
15" D.Fir at S.52°E., 16 lks. with healed face.  
16" Hemlock at N.7 3/4°E., 20 lks. with healed face.  
2" Alum. cap LS 498 on 5/8" iron rod at S.0°15'E., .08 chs.

New BT - 14" D.Fir N.61°W., 26.7 ft. to spike driven in side center, mkd. "T29R8S33 BT" with BT tag.

FD. & used by BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1972, surveyed April/May 2001- (DCSO rec. Vol. 54 Page(s) 20953)