

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6590)

Set ¼ sec. post, from which
A Laurel 9" dia., bears S.73°W., 20 lks. dist.
A Laurel 10" dia., bears N.13°E., 8 lks. dist.

Survey by Burton Holt - For: Sun Studs, Inc. - Sept. 1976 - M 61-78

Found - Iron pipe, unrecorded.
20" Madrone, bears N.13½°E., 8 lks., original.
Set 1" x 40" Iron pipe.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2196, Surveyed Feb/March 2008 - (DCSO records Vol. 56 Page(s) 22279-80)

The ¼ sec. cor. of secs. 33 & 34, perpetuated by person(s) unknown, monumented with an iron pipe, 1¼" dia., loosely set and bent, projecting 14" above the ground, from which the remains of an original bearing tree
A madrone stump, 26" dia., bears N.13°E., 5.3 ft., with fragmentary scribe marks visible on an open blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 18" in the ground, in a mound of stone, 2½ ft. base. to top, with brass cap mkd.
T29S R8W
¼
S 33|S 34
2008

from which
A fir, 19" dia., bears S.1°E., 71.4 ft., mkd. ¼ S34 BT.
An oak, 9" dia., bears N.47°W., 16.0 ft., mkd. ¼ S33 BT.
Bury the existing iron pipe, 30" long, inside and deposit a magnet in a white plastic case at the base of the stainless steel post.

1